## SATCO NUVO

Project Name

Prepared By



Notes

General	
Status	Active
Watts	13.5W
HID Equivalent	50W
Volts	120V-277V
Shape	ED17
Base	Medium
ANSI Base	E26
Finish	Clear
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	2000L
Beam Spread	320
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	LED HID
Technology	LED
Min Compartment Size	Length: 5.98 in. Width: 5.98 in. Height: 10.16 in.
Ballasting Requirements	Ballast Bypass
Electrical	
Operating Frequency	60Hz
Operating Frequency Power Factor	60Hz
Power Factor	
Power Factor Operating Position	0.9 Universal
Power Factor	0.9
Power Factor Operating Position Surge Protection Operating Temperature	0.9 Universal Built-in surge protection - 4KV
Power Factor Operating Position Surge Protection Operating Temperature Physical	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F)
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F)  5.8
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F)  5.8 2.13
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F)  5.8
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F)  5.8 2.13
Power Factor Operating Position Surge Protection Operating Temperature  Physical MOL MOD Weight (lb.)	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F)  5.8 2.13
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F)  5.8 2.13 0.25
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F)  5.8 2.13 0.25
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture IP Rating	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F)  5.8 2.13 0.25  Yes IP65
Power Factor Operating Position Surge Protection Operating Temperature  Physical  MOL  MOD  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  IP Rating Installation Notes  Warranty	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F)  5.8 2.13 0.25  Yes IP65 Not for use in vapor tight fixtures.
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture IP Rating Installation Notes	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F)  5.8 2.13 0.25  Yes IP65 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro
Power Factor Operating Position Surge Protection Operating Temperature  Physical  MOL  MOD  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  IP Rating Installation Notes  Warranty  Compliance  Safety Listing	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F)  5.8 2.13 0.25  Yes IP65 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro  CULus - Certified; cULus - Classified; cULus - Listed
Power Factor Operating Position Surge Protection Operating Temperature  Physical  MOL  MOD  Weight (lb.)  Additional Information Rated For Enclosed Fixture  IP Rating Installation Notes Warranty  Compliance  Safety Listing Location Rating	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F)  5.8 2.13 0.25  Yes IP65 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro  CULus - Certified; cULus - Classified; cULus - Listed Wet
Power Factor Operating Position Surge Protection Operating Temperature  Physical  MOL  MOD  Weight (lb.)  Additional Information Rated For Enclosed Fixture IP Rating Installation Notes Warranty  Compliance  Safety Listing Location Rating DLC Approved	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F)  5.8 2.13 0.25  Yes IP65 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro  CULus - Certified; cULus - Classified; cULus - Listed Wet No
Power Factor Operating Position Surge Protection Operating Temperature  Physical  MOL  MOD  Weight (lb.)  Additional Information Rated For Enclosed Fixture  IP Rating Installation Notes Warranty  Compliance  Safety Listing Location Rating	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F)  5.8 2.13 0.25  Yes IP65 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro  CULus - Certified; cULus - Classified; cULus - Listed Wet