SATCO NUVO

Project Name

ocation Prepared By



Notes

v] 02-25-2025 19:07:4

General	
Status	Active
Watts	34W
HID Equivalent	150W
Volts	120V-277V
Shape	ED28
Base	Mogul Extended
ANSI Base	EX39
Finish	White
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	5000L
Beam Spread	320
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	LED HID
Technology	LED
Min Compartment Size	Length: 9.25 in. Width: 9.25 in. Height: 17.28 in.
Ballasting Requirements	Ballast Bypass
Electrical	
Operating Frequency	60Hz
	60Hz 0.9
Operating Frequency	
Operating Frequency Power Factor	0.9
Operating Frequency Power Factor Operating Position	0.9 Universal
Operating Frequency Power Factor Operating Position Surge Protection	0.9 Universal Built-in surge protection - 4KV
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F)
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F)
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 8.4 3.54
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Weight (lb.)	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F)
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Weight (lb.) Additional Information	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 8.4 3.54 0.68
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 8.4 3.54 0.68
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 8.4 3.54 0.68 Yes IP65
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Installation Notes	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 8.4 3.54 0.68 Yes IP65 Not for use in vapor tight fixtures.
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 8.4 3.54 0.68 Yes IP65
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Installation Notes	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 8.4 3.54 0.68 Yes IP65 Not for use in vapor tight fixtures.
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Installation Notes Warranty	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 8.4 3.54 0.68 Yes IP65 Not for use in vapor tight fixtures.
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 8.4 3.54 0.68 Yes IP65 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro CULus - Certified; cULus - Classified; cULus -
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 8.4 3.54 0.68 Yes IP65 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro CULus - Certified; cULus - Classified; cULus - Listed
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 8.4 3.54 0.68 Yes IP65 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro CULus - Certified; cULus - Classified; cULus - Listed Wet
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating California Status	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 8.4 3.54 0.68 Yes IP65 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro CULus - Certified; cULus - Classified; cULus - Listed Wet Lawful for sale in California
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status	0.9 Universal Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 8.4 3.54 0.68 Yes IP65 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro CULus - Certified; cULus - Classified; cULus - Listed Wet Lawful for sale in California Lawful for sale