

DR50 Standard Duty - 50 A

UL/CSA Ratings

- Max Amperage & Voltage**
 50 A, 600 VAC
- Current Interruption Capability**
 For current interrupting up to 250 VAC
 For Switch-Rated devices, see DSN & DS sections.
- Short Circuit Rating**
 100 kA
 Testing was performed with RK1 current limiting Mersen fuses sized at least 100% of the device's ampacity rating.
- Environmental Ratings**
 Type 3R (Standard)
 Type 4X (Optional)
- Temperature Range**
 Min -40°F/Max 140°F
 See pg 260 for temperatures outside of this range.
- Wiring Capacity**
 Based on THHN wire sizes.
 Min 14 AWG Max 4 AWG
 Aux Contacts: Max 14 AWG
- Certifications**
 UL 1682, CSA C22.2 NO. 182.1, NOM

Receptacle (female)



Inlet (male)



! Remember to add installation accessories to your order

North American UL/CSA Configurations

| VOLTAGE | POLARITY | PART # POLY | PART # POLY |
|-----------|----------|----------------|----------------|
| 120 V | 1P+N+G | 31-34235-K16 | 31-38235-K16 |
| 120 208 V | 3P+N+G | 31-34237-K16 | 31-38237-K16 |
| 125 V | 1P+N+G | 31-34175-K07 | 31-38175-K07 |
| 125 250 V | 2P+N+G | 31-34176-K07 | 31-38176-K07 |
| 208 V | 2P+G | 31-34232-K16 | 31-38232-K16 |
| 208 V | 3P+G | 31-34233-K16 | 31-38233-K16 |
| 250 V | 2P+G | 31-34172-K07 | 31-38172-K07 |
| 250 V | 3P+G | 31-34173-K07 | 31-38173-K07 |
| 277 V | 1P+N+G | 31-34245-K04 | 31-38245-K04 |
| 277 480 V | 3P+N+G | 31-34247-K04 | 31-38247-K04 |
| 347 600 V | 3P+N+G | 31-34187-K14 | 31-38187-K14 |
| 480 V | 2P+G | 31-34242-K04 | 31-38242-K04 |
| 480 V | 3P+G | 31-34243-K04 | 31-38243-K04 |
| 600 V | 2P+G | 31-34182-K14 | 31-38182-K14 |
| 600 V | 3P+G | 31-34183-K14 | 31-38183-K14 |

For international configurations and ratings (IEC, CE) visit meltric.com/international-catalog or contact Customer Service at 800-433-7642.

Main Options



Auxiliary/Pilot Contacts



Mushroom Pawl



Padlock Pawl



Self-Returning Lid
 Recommended for cord applications to keep lid tucked in to avoid damage.

RECEPTACLE OPTIONS

SUFFIX

INLET OPTIONS

SUFFIX

| | | | |
|-----------------------------------|------------------------------------|--|-----------------------------------|
| With 2 Auxiliary/Pilot Contacts | Recept # -972 | With 2 Auxiliary/Pilot Contacts | Inlet # -972 |
| With 3 Auxiliary/Pilot Contacts | Recept # -973 | With 3 Auxiliary/Pilot Contacts | Inlet # -973 |
| With 4 Auxiliary/Pilot Contacts | Recept # -974 | With 4 Auxiliary/Pilot Contacts | Inlet # -974 |
| Type 4X & Self-Returning Lid | Recept # -4X | Type 4X Watertightness | Inlet # -4X |
| Mushroom Pawl | Recept # -375 | Without Lockout Hole | Inlet # -A155 |
| Padlock Pawl | Recept # -843 | For Microswitch | Inlet # -270^{3,4} |
| Screw-Type Locking Pawl | Recept # -845 | Notes: | |
| Metal Pawl (on poly receptacle) | Recept # -824 | ³ Not UL/CSA listed. | |
| Self-Returning Lid (Manual Close) | Recept # -NC | ⁴ Not available on 3P+N+G configurations. | |
| With Microswitch | Recept # -270^{3,4} | | |

! See pages 237-246 for detailed information on these options

Order Example: 480 V DR50 + 2 auxiliary contacts

DR50 Poly inlet 3P+G = 31-38243-K04-972



INSTALLATION ACCESSORIES – SIZE 3

When properly installed, all accessories meet or exceed the environmental ratings of the devices they are mounted to; unless otherwise noted.

| HANDLES | HANDLE WITH NPT | | PART # POLY | PART # METAL |
|---------|-----------------|----------|-------------|--------------|
| | | 1/2" | 513P0N05 | 593P0N05 |
| | 3/4" | 513P0N07 | 593P0N07 | |
| | 1" | 513P0N10 | 593P0N10 | |
| | 1 1/4" | 513P0N12 | 593P0N12 | |

For available cord grips, see pg 231.

| POLY HANDLE WITH CORD GRIP | CABLE RANGE | PART # |
|----------------------------|-------------|----------|
| | .520-.680" | 713P0CP5 |
| | .680-.980" | 713P0DP4 |
| | .980-1.260" | 713P0EP4 |

| METAL HANDLE WITH CORD GRIP | CABLE RANGE | PART # |
|-----------------------------|--------------|----------|
| | .635-.750" | 793P0CS4 |
| | .770-.850" | 793P0DS1 |
| | .875-1.000" | 793P0DS3 |
| | 1.000-1.125" | 793P0ES2 |

| POLY HANDLE | CABLE RANGE | PART # |
|-------------|-------------|----------|
| | .390-1.180" | 513P0D30 |

| POLY HANDLE WITH BUILT IN DRAWPLATES | CABLE RANGE | PART # |
|--------------------------------------|-------------|-------------|
| | .390-1.180" | 513P0D30473 |

Makes connector closures easier.

| POLY HANDLE WITH CLAMP & BUSHING | CABLE RANGE | PART # |
|----------------------------------|--------------|----------|
| | .750-.875" | 713P0S14 |
| | .875-1.000" | 713P0S16 |
| | 1.000-1.125" | 713P0S18 |
| | 1.125-1.250" | 713P0S20 |
| | 1.250-1.375" | 713P0S22 |

| ANGLES | POLY ANGLE | | PART # | Notes |
|--------|------------|-----|--------|-------|
| | | 30° | 513M3 | 513M7 |
| | 70° | | | |

| METAL ANGLE | ANGLE | PART # | Notes |
|-------------|-----------|---------|--|
| | 0° | 593M0 | |
| | 30° | 593M3 | |
| | FS/FD 30° | 793M3FS | Base measures approximately 4.2" x 2.7". Due to the variation in sizes of FS boxes, please verify that your FS box matches our dimensions, if not call Customer Service for other solutions. |
| | 70° | 593M7 | |

| BOXES | POLY CONDUIT ENTRY WITH NPT | | PART # | Notes |
|-------|-----------------------------|-----|----------|----------|
| | | 30° | 3/4" | 513B3N07 |
| | 30° | 1" | 513B3N10 | |

| POLY WALL BOX WITH ANGLE | ANGLE | PART # | Notes |
|--------------------------|-------|----------|---|
| | 70° | 513C7000 | 70° poly boxes are not drilled. * Interior volume with receptacle installed. |

| POLY ANGLE WITH METAL BOX WITH NPT | ANGLE | CABLE RANGE | PART # | Notes |
|------------------------------------|-------|-------------|----------|--|
| | 70° | 1/2" | 713C7N05 | * Interior volume with receptacle installed. |
| | 70° | 3/4" | 713C7N07 | |
| | 70° | 1" | 713C7N10 | |
| | 70° | 1 1/4" | 713C7N12 | |
| | 70° | 1 1/2" | 713C7N15 | |

| METAL BOX WITH NPT | ANGLE | CABLE RANGE | PART # |
|--------------------|-------|-------------|----------|
| | 0° | 1/2" | 7T1F0N05 |
| | 0° | 3/4" | 7T1F0N07 |
| | 0° | 1" | 7T1F0N10 |
| | 0° | 1 1/4" | 7T1F0N12 |

| POLY ANGLE WITH METAL BOX WITH NPT | ANGLE | CABLE RANGE | PART # | Notes |
|------------------------------------|-------|-------------|----------|---|
| | 30° | 1/2" | 713C3N05 | For metal angle, replace "71" prefix with "79". * Interior volume with receptacle installed. |
| | 30° | 3/4" | 713C3N07 | |
| | 30° | 1" | 713C3N10 | |
| | 30° | 1 1/4" | 713C3N12 | |

NPT on top or bottom (if rotated). For other configurations, contact Customer Service.

| MISCELLANEOUS ACCESSORIES | Part # | Description |
|---------------------------|----------|--|
| | 61-6A346 | Set of Two (2) Recommended for all assembly applications, for facilitated mating. |

| PROTECTIVE INLET/PLUG CAP | Part # | Description |
|---------------------------|----------|------------------------|
| | 31-3A426 | For Inlets/Plugs Only. |

| PADLOCKABLE INLET/PLUG CAP | Part # | Description |
|----------------------------|--------|-------------------------------|
| | DS3PC | Poly - For Inlets/Plugs Only. |

| SPRING-LOADED PADLOCKABLE INLET/PLUG CAP | Part # | Description |
|--|----------|---|
| | 31-3A226 | For Inlets/Plugs Only. In order to achieve max water ingress protection of Type 3R/IP55, spring loaded caps should be ordered with inlets equipped with -A155 suffix. |

| EASY RETROFIT ADAPTER PLATES | Part # | Description |
|------------------------------|------------|--------------------------|
| | see pg 246 | Mount to existing boxes. |

| RECEPTACLE LOCKING PIN | Part # | Description |
|------------------------|--------|--|
| | LP-843 | Requires Padlockable Pawl option (-843) on receptacle. |