

ACCESSORIES  
XS-100 FASTRAP®  
FEATURES

- Requires less than half the time to mount/dismount compared to ordinary brackets.
- Compatible with nearly all distribution-type stringing blocks.
- One model fits all cross-arm sizes.
- No tools needed to mount or dismount.
- Strong holding force, without damage, regardless of materials.

COMPLETE DIMENSIONS

| XS-100 FASTRAP                         |   |
|--|---|
| Pulling Load, rated                    | 2,500 lb., vertical; 1,500 lb., horizontal  |
| Compatible Cross-Arm Size, max.        | 4 in. x 10 in.  |
| Compatible Cross-Arm Size, min.        | 3 1/2 in. x 4 1/2 in.   |
| Operating Mechanism                    | Encircling strap with manual tightening using a fine-tooth ratcheted lever; released by quick-release lever |
| Base                                   | Aluminum, with slip-resistant coating   |
| Strap                                  | 30 in. length, Polyester, woven, with UV inhibitors & wear indicators                                       |
| Strap-Assembly Breaking Strength, min. | 9,000 lb.   |
| Ratchet Material                       | Steel, with corrosion-resistant coating   |
| Weight, nom.                           | 6 1/2 lb.   |
| Dimensions, stored, nom.               | 12 in. x 7 1/4 in. x 6 in.  |

