



Hospital Products

15 and 20 Ampere, 125 Volts



USB8300CPDW



USB8200CPDW

Hospital Grade USB-C Power Delivery Charger Type C and Type A&C






Hospital Grade USB-C Power Delivery Charger Receptacle, two Type-C port configurations, one USB-C Power Delivery port with up to 55 Watt output and one USB Type-C convenience port with up to 1.5 Amp, 5 Volt output, USB ports rated 10,000 cycles.




Hospital Grade USB-C Power Delivery Charger Receptacle, one Type A and one Type C port configurations, one USB-C Power Delivery port with up to 55 Watt output and one USB Type-A convenience port with up to 1.5 Amp, 5 Volt output, USB ports rated 10,000 cycles.

Description	Color	Catalog Number	
Hospital Grade USB-C Power Delivery Charger Receptacle, two Type-C port configurations, one USB-C Power Delivery port with up to 55 Watt output and one USB Type-C convenience port with up to 1.5 Amp, 5 Volt output, USB ports rated 10,000 cycles.	Black	USB8200CPDBK	USB8300CPDBK
	Brown	USB8200CPD	USB8300CPD
	Gray	USB8200CPDGY	USB8300CPDGY
	Ivory	USB8200CPDI	USB8300CPDI
	Light Almond	USB8200CPDLA	USB8300CPDLA
	Red	USB8200CPDR	USB8300CPDR
	White	USB8200CPDW	USB8300CPDW
Hospital Grade USB-C Power Delivery Charger Receptacle, one Type A and one Type C port configurations, one USB-C Power Delivery port with up to 55 Watt output and one USB Type-A convenience port with up to 1.5 Amp, 5 Volt output, USB ports rated 10,000 cycles.	Black	USB8200ACPDBK	USB8300ACPDBK
	Brown	USB8200ACPD	USB8300ACPD
	Gray	USB8200ACPDGY	USB8300ACPDGY
	Ivory	USB8200ACPD	USB8300ACPD
	Light Almond	USB8200ACPDLA	USB8300ACPDLA
	Red	USB8200ACPDR	USB8300ACPDR
	White	USB8200ACPDW	USB8300ACPDW


Note: See page A-7 for additional information on USB charger devices.



HBL420HS



HBL415HI



HBL4API

4-PLEX® Hospital Grade Receptacles



Description	Color	Catalog Number	
4 outlet high impact resistant Polycarbonate construction. Mount to 4 in. square box.	Brown	HBL415H	HBL420H
	Gray	—	HBL420HGY
	Ivory	HBL415HI	HBL420HI
	Red	HBL415HR	HBL420HR
	White	HBL415HW	HBL420HW
4-PLEX surge protection receptacles with lights, 80 joules, 6.5kA peak current.	Blue	—	HBL420HS
	Ivory	—	HBL420HIS
	Red	—	HBL420HRS

4-PLEX® Accessories

Description	Color	Catalog Number
4-PLEX adapter plates for 1- and 2-gang, device boxes.	Blue	HBL4APBL
	Brown	HBL4AP
	Gray	HBL4APGY
	Ivory	HBL4API
	Orange	HBL4APO
	Red	HBL4APR
	White	HBL4APW
4-PLEX Portable Box, 4 in. (101.6) square box with cord grip. Accepts up to .66 in. (16.8) diameter cord.	Black	HBL4PBBK
	Brown	HBL4PB
	Ivory	HBL4PBI

Note: 4-PLEX Box is not UL listed or CSA Certified. UL listing does not apply when 4-PLEX Receptacle is used with 4-PLEX Box in extension cord application. Supplied with one cord clamp.

Dimensions in Inches (mm)