

# DELIVERY | SystemOne 8<sup>+</sup>/10-Gang Recessed Floor Boxes



Dimensions		Inches (mm)		
Style	Rectangular Cover		Round Cover	
<b>Box Type</b>				
Standard Box Corrosion-Resistant Box (On-grade)	CFB10G55E -	- CFB10G55CRE	CFB10G55RE -	- CFB10G55RCRE
<b>Recommended Pour Depth</b>	6.00" (152.4)	6.00" (152.4)	6.25" (158.8)	6.25" (158.8)
<b>Min. Depth of Pour</b>	5.50" (139.7)	5.50" (139.7)	6.25" (158.8)	6.25" (158.8)
<b>Adjustability</b>	Fully	Fully	Fully	Fully
<b>Cubic Inch (cm<sup>3</sup>) Capacity per Gang</b>	35.0/69.5/99.0 cu. in.	35.0/69.5/99.0 cu. in.	99/105 cu. in.	35.0/69.5/99.0 cu. in.
	(574/1139/1622 cm <sup>3</sup> )	(574/1139/1622 cm <sup>3</sup> )	(1621/1721 cm <sup>3</sup> )	(574/1139/1622 cm <sup>3</sup> )
<b>Dimensions - A</b>	5.59" (142.0)	5.59" (142.0)	-	-
<b>Dimensions - B</b>	11.09" (281.6)	11.09" (281.6)	11.09" (281.6)	11.09" (281.6)
<b>Dimensions - C</b>	14.14" (359.2)	14.14" (359.2)	14.14" (359.2)	14.14" (359.2)
<b>Dimensions - D</b>	-	-	8.37" (212.5) TYP.	8.37" (212.5) TYP.
<b>Dimensions - E</b>	5.50" (139.7)	5.50" (139.7)	6.25" (158.8)	6.25" (158.8)
<b>KO Trade Size: Ends Sides Bottom</b>	(2) 1/2", 3/4", (4) 1/2", 3/4", 1", 1 1/4", 1 1/2" (2) 3/4", 1", 1 1/4", 2"* (2) 1/2", 3/4", (4) 1/2", 3/4", 1", 1 1/4"	(2) 1/2", 3/4", (4) 1/2", 3/4", 1", 1 1/4", 1 1/2" (2) 3/4", 1", 1 1/4", 2"* (2) 1/2", 3/4", (4) 1/2", 3/4", 1", 1 1/4"	(2) 1/2", 3/4", (4) 1/2", 3/4", 1", 1 1/4", 1 1/2" (2) 3/4", 1", 1 1/4", 2"* (2) 1/2", 3/4", (4) 1/2", 3/4", 1", 1 1/4"	(2) 1/2", 3/4", (4) 1/2", 3/4", 1", 1 1/4", 1 1/2" (2) 3/4", 1", 1 1/4", 2"* (2) 1/2", 3/4", (4) 1/2", 3/4", 1", 1 1/4"
<b>Cover Style</b>	Rectangular	Rectangular	Round	Round
<b>2 Inch Hub Compatible</b>	Yes	Yes	Yes	Yes

Note: \*Requires CFBHUB2 for 2" conduits. CFBHUB200PVC for 2" PVC conduits or CFBHUB125PVC for 1 1/4" PVC conduits.

## Rectangular Covers

- Compatible with CFB10G55 and CFB10G55CR Series Floor Boxes
- Two large cable egress doors and access 180° opening
- Maximum static load of 1500lb with 2x safety factor<sup>†</sup>
- Surface style typical applications: carpet, VCT
- Flush style typical applications: tile, finished concrete and terrazzo floors
- Furniture Feed covers dividers purchased separately

Surface Cover Flange Dimensions 11 1/2" x 10"						Flush Cover Flange Dimensions 10 1/2" x 9"		
Finish	Without Insert	With Insert	Furniture Feed ((2)1 in. and (2) 2 in. Plugs)	Without Insert	With Insert	Furniture Feed ((2)1 in. and (2) 2 in. Plugs)		
Aluminum Powder Coat	610GCCVRLU	610GCCVRLUC	610GCCFFCVRALU*	610GTCVRLU	610GTCVRLUC	610GTFFCVRALU*		
Black Powder Coat	610GCCVRBK	610GCCVRBKC	610GCCFFCVRBK*	610GTCVRBK	610GTCVRBKC	610GTFFCVRBK*		
Brass Powder Coat	610GCCVRBRS	610GCCVRBRSC	610GCCFFCVRBRS*	610GTCVRBRS	610GTCVRBRSC	610GTFFCVRBRS*		
Bronze Powder Coat	610GCCVRBRZ	610GCCVRBRZC	610GCCFFCVRBRZ*	610GTCVRBRZ	610GTCVRBRZC	610GTFFCVRBRZ*		
Satin Nickel Powder Coat	610GCCVRNK	610GCCVRNKC	610GCCFFCVRNK*	610GTCVRNK	610GTCVRNKC	610GTFFCVRNK*		

Note: \* For 10-gang box dual service, **CFB10FFDIVKIT** required with Furniture Feed covers. Purchased separately.



## Round Covers

- Compatible with CFB10G55R and CFB10G55RCR Series Floor Boxes
- Two large cable egress doors and access 180° opening
- Maximum static load of 1,000 lbs. with 2x safety factor<sup>†</sup>
- Recessed covers- 180° access with 2 cable egress doors
- Furniture Feed covers dividers purchased separately

Finish	Surface	Furniture Feed (1 in. and 2 in. Plugs)		
Brushed Aluminum	CFBS1R8CVRALU	CFBS1R8FFCVRALU#		
Black Powder Coated	CFBS1R8CVRBLK	CFBS1R8FFCVRBLK#		
Brass Plated	CFBS1R8CVRBRS	CFBS1R8FFCVRBRS#		
Bronze Plated	CFBS1R8CVRBRZ	CFBS1R8FFCVRBRZ#		
Gray Powder Coat	CFBS1R8CVRGRY	CFBS1R8FFCVRGRY#		
Satin Nickel Plated	CFBS1R8CVRNKL	CFBS1R8FFCVRNKL#		



<sup>†</sup> Load applied through a 3" (76mm) mandrel in center of the cover

\*For 10-gang box dual service, **CFBS1R8FF10GDIVKIT** required with Furniture Feed covers. Purchased separately.

<sup>†</sup>UL File Number E31999. Boxes include concrete covers. FB10MPNEMA2XG and/or FB10MPNEMA4G for 8-gang configuration.

**ScrubShield®**

Complies with UL514 A