SpikeShield® Power Quality Products









Circuit Guard [®] , Specification Grade Duplex Receptacles		15A 125V NEMA 5-15R UL CSA	20A 125V NEMA 5-20R UL CSA
Description	Color	Catalog Number	
Surge protection receptacles with light,	Blue	HBL5260SA	HBL5360SA
240 joules, 15kA peak current.	lvory	HBL5260ISA	HBL5360ISA
	Office White	HBL5260OWSA	HBL5360OWSA
	White	HBL5260WSA	HBL5360WSA
Surge protection receptacles with light	Blue	HBL5262SA	HBL5362SA
and alarm, 240 joules, 15kA peak current.	Gray	HBL5262GYSA	HBL5362GYSA
	Ivory	HBL5262ISA	HBL5362ISA
	Office White	HBL5262OWSA	HBL5362OWSA
	White	HBL5262WSA	HBL5362WSA
Isolated ground, surge protection	Blue	IG5262SA	IG5362SA
receptacles with light and alarm,	Gray	IG5262GYSA	IG5362GYSA
240 joules, 15kA peak current.	lvory	IG5262ISA	IG5362ISA
, , , , ,	Office White	IG5262OWSA	IG5362OWSA
	Orange	IG5262OSA	IG5362OSA
	White	IG5262WSA	IG5362WSA
4-PLEX® surge protection receptacles	Blue	HBL415S	HBL420S
with lights, 80 joules, 6.5kA peak current.	lvorv	HBL415IS	HBL420IS



HBL5262GYSA

3.28" | (83.3) 2.62" (66.5)

IG5362SA



HBL8362ISA

-3.38" (85.9) -3.02" (76.7)

Circuit Guard®, Hospital Grade Duplex Receptacles

Circuit Guard , Hospital Grade Duplex neceptacles					
Description	Color	Catalog Number			
Surge protection receptacles with light	Blue	HBL8262SA	HBL8362SA		
and alarm, 240 joules, 15kA peak current.	Gray	HBL8262GYSA	HBL8362GYSA		
	lvory	HBL8262ISA	HBL8362ISA		
	Red	HBL8262RSA	HBL8362RSA		
	White	HBL8262WSA	HBL8362WSA		
Isolated ground, surge protection	Blue	IG8262SA	IG8362SA		
receptacles with light and alarm,	Gray	IG8262GYSA	IG8362GYSA		
240 joules, 15kA peak current.	lvory	IG8262ISA	IG8362ISA		
	Orange	IG8262OSA	IG8362OSA		
	Red	IG8262RSA	IG8362RSA		
	White	IG8262WSA	IG8362WSA		
4-PLEX surge protection receptacles	Blue	_	HBL420HS		
with lights, 80 joules, 6.5kA peak current.	lvory	_	HBL420HIS		
	Red	_	HBL420HRS		

4-PLEX® Accessories

TILEX ACCESSORES		
Description	Color	Catalog Number
4-PLEX adapter plates for 1- and 2-gang	Blue	HBL4APBL
(4-PLEX mount directly to 4" (101.6) square	lvory	HBL4API
device boxes).	Red	HBL4APR
4-PLEX portable box. Portable 4" (101.6) square box	lvory	HBL4PBI
with one cord grip. Accepts up to .66" (16.8) dia. cord.		

Note: 4-PLEX box is not UL Listed.

Wallplates (Sold Separately)

wanpiates (ooid ooparately)							
Configuration	High-Impact Thermoplastic Color Standard Mid-Size		Plated Steel		Stainless Steel (S/S) Brass		
1-Gang	Blue Gray Ivory Ivory Orange Red White	P26GY P26I P26OIG** P26R P26W	PJ26BL PJ26GY PJ26I PJ26C* - PJ26R PJ26W	Chrome Brass Plated	SCH26 SBP26	Smooth S/S Smooth S/S Smooth Brass	SS26 SSJ26 A SB26

4.30" sq. (109.2) (23.4)

HBL415S

Dimensions in Inches (mm)

Note: *Premarked "COMPUTER ONLY." Lettering is block ¼" high.
**Premarked "ISOLATED GROUND." Lettering is block ¼" high.

▲ Jumbo size plate.

See section O for additional wallplates.

(2.5)