



DATE: LOCATION: TYPE: PROJECT:

CATALOG #:





FEATURES

- · Edge-Lit technology for even illumination
- Low profile 2.1" depth design virtually disappears into the canopy
- · Illuminates without distraction and glare
- Pendant or surface mounted with 3/4" conduit
- Universal retrofit solution for HID replacements for various sizes
- · IP66 rating to keep water and insects out
- Cast Aluminum with integral heat sink to maintain optimal thermal performance for long LED life Cast aluminum









SPECIFICATIONS

CONSTRUCTION

- · Die-cast aluminum, low profile housing
- · New construction or retrofit solution
- · Canopy and soffit applications
- · Easy installation
- Driver and optical chamber serviceable from below canopy
- · Powder coat finish
- Heat sink design to disperse heat away from fixture
- Suitable for wet locations

OPTICS

- Acrylic Lens
- Type V distribution
- Comfort lens for low glare
- · Light Guide Edge-Lit technology

INSTALLATION

- · Surface or pendant mounted
- Easy installation and serviceable below the canopy deck
- · Hinge for hanging during service

ELECTRICAL

- Universal 120-277, 347, 480 Input Voltage
- Power Factor > 0.9 at full load
- Total Harmonic Distortion < 20% at full load
- 10 kV Surge Protection
- 0-10 Volt Dimmable Driver
- Operating temperature: -40°C to +40°C

CERTIFICATIONS

- · UL Certified
- DesignLights Consortium[™] 5.1 qualified
- · Wet Location Listed
- IP66
- DLC® (DesignLights Consortium Qualified), with some Premium Qualified configurations.
 Please refer to the DLC website for specific product qualifications at www.designlights.org

WARRANTY

• 5 year warranty

ORDERING GUIDE

CATALOG #

VSH		_		_			_		
Series	Wattage	ttage Color Temp Voltage		je	Finis				
VSH Vanish	30¹		4K7		UNV	Universal		BLT	Black Matte Textured
	55		5K7		347	347V		BLS	Black Gloss Smooth
	85				480	480V		DBT	Dark Bronze Matte Texture
	140							DBS	Dark Bronze Gloss Smooth
								GTT	Graphite Matte Textured
								LGS	Light Grey Gloss Smooth
								LGT	Light Grey Matte Textured
								PSS	Platinum Silver Smooth
								WHT	White Matte Textured
								WHS	White Gloss Smooth
								VGT	Verde Green Textured
								Color	Option
								СС	Custom Color

Notes:

Only available in Universal Voltage

KEY DATA				
Lumen Range	4,500 – 20,200			
Wattage Range	30 – 140 Watts			
Efficacy Range (LPW)	138 – 157			
Reported Life (Hours)	>60,000			

Example: VSH-85-5K7-UNV-WHS





design . performance . technology
Vanish
EDGE-LIT CANOPY

DATE:	LOCATION:				
TYPE:	PROJECT:				

CATALOG #:

PERFORMANCE DATA

Product	Lumens	В	U	G	LPW	CRI	сст
VSH-30-4K7	4564	2	0	1	150	70	4000K
VSH-30-5K7	4793	2	0	1	157	70	5000K
VSH-55-4K7	8846	3	0	2	153	70	4000K
VSH-55-5K7	9069	3	0	2	157	70	5000K
VSH-85-4K7	13296	3	0	2	152	70	4000K
VSH-85-5K7	13666	3	0	2	157	70	5000K
VSH-140-4K7	19649	4	0	3	138	70	4000K
VSH-140-5K7	20196	4	0	3	142	70	5000K

Data is considered to be representative of the configurations shown. Actual performance may differ as a result of end-user environment application and inherent performance balances of the electrical components.

PROJECTED LUMEN MAINTENANCE

A made i a mat	OPERATING HOURS								
Ambient Temperature	0	25,000	50,000	TM-21-11 ¹ L96 60,000	100,000	L70 (Hours)			
25°C / 77°F	1.00	0.94	0.92	0.90	0.81	>170,000			
40°C / 104°F	0.99	0.94	0.92	0.89	0.80	>160,000			

LUMINAIRE AMBIENT TEMPERATURE FACTOR (LATF)

Ambient Te	emperature	Lumen Multiplier
0°C	32°F	1.03
10°C	50°F	1.01
20°C	68°F	1.00
25°C	77°F	1.00
30°C	86°F	0.99
40°C	104°F	0.98
50°C	122°F	0.97







DATE:	LOCATION:
TYPE:	PROJECT:

CATALOG #:

DIMENSIONS





MOUNTING ACCESSORIES

Accessories (order separately)						
93133148	WHITEWAY 15 IN CVR PLT WHT VSH/GSY	Retrofit cover plate for LSI Encore 15" square-replacement for 10" opening				
93133149	WHITEWAY DECORATIVE CVR PLT VSH/GSY	26" Decorative Beauty Plate for Canopy Retrofits				
93133151	WHITEWAY HID RETRFT KIT WHT VSH/GSY (fits any square HID housing between 21" & 23	Universal HID retrofit kit " square.)				
93133177	WHITEWAY STEM AND JUNCTION BOX					

93133148



• Measure outside dimension of existing housing



93133149



93133177

