



Lensed Strip

Selectable Lensed Strip

PROJECT INFORMATION

JOB NAME	
FIXTURE TYPE	Selectable Lensed Strip
CATALOG NUMBER	
APPROVED BY	

SPECIFICATIONS

Construction:

Rigid 24 gauge steel housing

Lightweight & durable

Polycarbonate Lens

Electrical:

AC Input: 120-347 V; 50/60Hz

Driver: Constant current, Class 2 output

High Efficiency Driver: minimum 85%

Dimming 0-10V

Temperatures: Min. -30°C (-22°F) Max: +50°C (+122°F)

LEDs:

3000K/3500K/4000K/5000K CCT

80 CRI

L70 Calculated Life: >50,000 Hours¹

Listings:

UL/cUL standards for damp locations

DLC qualified luminaire, eligible for rebates from DLC member utilities.


Warranty:

Five-year limited warranty




DIMENSIONS

4' - Weight: 3.4 lbs.



8' - Weight: 6.2 lbs.



¹Lumen maintenance values at 25°C are calculated per TM-21 based on LM-80 data and in-situ luminaire testing

Rebates and Incentives are available in many areas. Contact an Atlas Representative for more information.



Origin Series

Selectable Lensed Strip

ORDERING INFORMATION

ORST	4	S	4L				
PRODUCT SERIES	FIXTURE LENGTH	SELECTABLE	LUMEN PACKAGE	VOLTAGE	COLOR TEMP.	HOUSING COLOR	OPTIONS
ORST = Origin Series Lensed Strip	4 = 4 ft	S = Selectable	3-5L = 3,000-5,000 Lumen Selectable	Blank = 120-347V	blank = Selectable 3000K, 3500K, 4000K, 5000K	Blank = White	EB = 8W Emergency Battery Backup
	8 = 8 ft		8-10L = 8,000-10,000 Lumen Selectable				

PERFORMANCE DATA

LUMEN PACKAGE	FIXTURE LENGTH	CRI	3000K CCT		3500K CCT		4000K CCT		5000K CCT		WATTAGE
			DELIVERED LUMENS	EFFICACY (LPW)	DELIVERED LUMENS	EFFICACY (LPW)	DELIVERED LUMENS	EFFICACY (LPW)	DELIVERED LUMENS	EFFICACY (LPW)	
ORST4S3-5L	4 ft	80	2,729	137	2,860	145	2,901	149	2,889	147	20W
			3,975	130	4,229	140	4,315	145	4,228	139	30W
			5,125	122	5,465	134	5,594	140	5,465	133	40W
ORST8S8-10L	8 ft	80	8,472	141	9,065	151	9,242	154	9,005	150	60W
			9,300	133	10,043	143	10,211	146	9,996	143	70W
			10,161	125	10,931	135	11,188	138	10,922	136	80W

DLC PRODUCT INFORMATION

UNIT	4000K CCT	
	DLC PRODUCT ID	CLASSIFICATION
ORST4S3-5L	S-CWJB75	Standard
ORST8S8-10L	S-PC0Z1M	Standard

ACCESSORIES

	CATALOG #	DESCRIPTION
	ORST-BP4	4ft Beauty Plate (Covers 4 inches)
	ORST-BP8	8ft Beauty Plate (Covers 4 inches)
	ORST-CR	Continuous Row Alignment Plate (No screws - Surface Mount Only)
	ORST-TGJ	T-Grid Alignment Bracket Joiner (4ft/8ft only)
	ORST-TGE	T-Grid Alignment Bracket End (4ft/8ft only)
	ORST-CRC4	4ft Continuous Row Connector Kit (2 Cables with quick connects - 3 wire power, 2 wire dimming)
	ORST-CRC8	8ft Continuous Row Connector Kit (2 Cables with quick connects - 3 wire power, 2 wire dimming)