

### TYPE UCS

#### Features

- Manufactured from high strength aluminum alloy, rated for 600 volts, 90 °C
- Four OD sizes accommodate a wire range from 1000kcmil to #4
- Chamfered barrel
- Prefilled with DE-OX
- Solid barrier in center
- Color coded end caps inserted in barrel

#### Benefits

- Provides maximum conductivity and excellent crimping characteristics
- Requires only four installation dies to crimp fourteen conductor sizes.
- Provides easy conductor insertion
- Prevents oxides from forming
- Prevents dissimilar metals from coming into contact
- Prevents foreign materials from entering the connector prior to usage and color code identifies the proper compression die



Catalog Number	Wire Range	Dimensions			Installing Dies	Die Index
		L	O.D.	I.D.		
UCS-4-Z	4	3"	41/64	9/32	BG, 5/8, 8A	9
UCS-2-Z	2	3"	41/64	11/32	BG, 5/8, 8A	9
UCS-1/0-Z	1/0	3"	41/64	27/64	BG, 5/8, 8A	9
UCS-2/0-Z	2/0	4"	29/32	7/16	249, 840, TX, 76, 11A	13
UCS-3/0-Z	3/0	4"	29/32	1/2	249, 840, TX, 76, 11A	13
UCS-4/0-Z	4/0	4"	29/32	9/16	249, 840, TX, 76, 11A	13
UCS-250-Z	250kcmil	4"	29/32	19/32	249, 840, TX, 76, 11A	13
UCS-300-Z	300kcmil	5"	1-5/32	21/32	299, 655, 705, 1-1/8, 13A	14
UCS-350-Z	350kcmil	5"	1-5/32	45/64	299, 655, 705, 96, 1-1/8, 13A	14
UCS-500-Z	500kcmil	5"	1-5/32	27/32	299, 655, 705, 96, 1-1/8, 13A	14
UCS-600-Z	600kcmil	6"	1-39/64	59/64	301, 1-1/2, 140	18
UCS-700/750-Z	750kcmil - 700kcmil	6"	1-39/64	1-1/32	301, 1-1/2, 140, 72H	18
UCS-1000-Z	1000kcmil	7"	1-39/64	1-3/16	301, 1-1/2, 140, 72H	18