

Northbrook, Illinois • (847) 272-8800  
Melville, New York • (631) 271-6200  
Santa Clara, California • (408) 985-2400  
Research Triangle Park,  
North Carolina • (919) 549 1400  
Camas, Washington • (360) 817-5500



## CERTIFICATE OF COMPLIANCE

CERTIFICATE NUMBER: 031000-E2875

ISSUE DATE: October 3, 2000

Page 1 of 3

Issued to: Square D Company  
1601 Mercer Road  
lexington, KY. 40511 USA

Report Reference: E2875, March 4, 1998


This is to Certify that  
representative samples of: Enclosed Switches, types H221, H321, H361 and H361, suitable for use as  
service equipment. Catalog numbers may have suffix letters.

Have been investigated by Underwriters Laboratories Inc.® in accordance with the Standard(s)  
indicated on this Certificate.


Standard(s) for Safety: UL 98, Enclosed Switches

Additional Information: See Addendum

Only those products bearing the UL Listing Mark should be considered as being covered by  
UL's Listing and Follow-Up Service.

The UL Listing Mark generally includes the following elements: the symbol UL in a circle:  with the word "LISTED"; a control  
number (may be alphanumeric) assigned by UL; and the product category name (product identifier) as indicated in the appropriate  
UL Directory.

### **LOOK FOR THE UL LISTING MARK ON THE PRODUCT**

Engineer:   
Tom Skibbs  
Underwriters Laboratories Inc.

Review Engineer:   
Jake Killinger  
Underwriters Laboratories Inc.

A not-for-profit organization  
dedicated to public safety and  
committed to quality service



CERTIFICATE OF COMPLIANCE - ADDENDUM

CERTIFICATE NUMBER: 031000-E2875  
ISSUE DATE: October 3, 2000

Page 2 of 3

This is to verify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

RATINGS

Current: 30 A maximum


Short Circuit: When used with Class J or R fuses, fusible switches are suitable for use  
On circuits capable of delivering not more than 200,000 rms symmetrical  
Amperes.


When used with Class H or K fuses, fusible switches are suitable for use  
On circuits capable of delivering not more than 10,000 rms symmetrical  
Amperes.

Unfused switches are suitable for use on circuits capable of delivering not  
More than

- (a) 10,000 rms symmetrical amperes when protected by Class H or K fuses or
- (b) 100,000 rms symmetrical amperes when protected by Class J, T or R fuses.

---

Engineer:   
Tom Skibbs  
Underwriters Laboratories Inc.

Review Engineer:   
Jake Killinger  
Underwriters Laboratories Inc.



CERTIFICATE OF COMPLIANCE - ADDENDUM

CERTIFICATE NUMBER: 031000-E2875  
 ISSUE DATE: October 3, 2000

Page 3 of 3

This is to verify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

	Amps	Volts(max)	Horsepower (+ indicates maximum rating)									
			Current		Alternating						Direct	
			Voltage	Phase	120	240	480	600	125	250	600	
H221	30	240ac/250dc	.5, 2+	1.5, 3+	3, 7.5+					2, 3+	5	-
H321	30	240ac/250dc	.5, 2+	1.5, 3+	3, 7.5+					2, 3+	5	-
H361	30	600ac/600dc	.5, 2+	1.5, 3+	3, 7.5+	3, 7.5+	5, 15+	3, 10+	7.5, 20+	2, 3+	5	10 15+
HU361	30	600ac/600dc	2	5	10	7.5	20	10	30	3	5	15

Engineer: *Tom Skibbs*  
 Tom Skibbs  
 Underwriters Laboratories Inc.

Review Engineer: *Jake Killinger*  
 Jake Killinger  
 Underwriters Laboratories Inc.