

USB RECHARGEABLE

INTRINSICALLY SAFE MULTI-FLOOD HEADLAMP

XPR-5552G

NIGHTSTICK®
Life Depends on Light

The world's first Class I, Division 1 / Zone 0/20 certified headlamp featuring independent white, red, and green multi-flood outputs with USB-C rechargeability.



Runs 8 hrs on white light in high and 12.5 hrs on red/green for **full shift battery**



Red **charging indicator light** turns green when fully charged via included USB-C cable



Floodlight tilts up and down to aim light exactly where needed



Left switch **cycles between red and green modes**. Right switch activates **white light** low and high mode

CERTIFIED



200 LUMENS

1-800-233-2155 • 1-469-326-9400 • nightstick.com

© 2025 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates.

MULTI-FLOOD HEADLAMP

LiPo BATTERY (INTEGRATED)

ITEM NUMBER/UPC

- XPR-5552, UPC 0 17398 80973 3

MARKET APPLICATIONS

- Confined space entry, hazardous work environments, oil & gas, petrochemical processing, industrial manufacturing, utilities, marine safety, aviation maintenance, and fire & rescue

CERTIFICATIONS

- Class I, Div 1 (cETLus) | ATEX & IECEx Zone 0/20

CASE MATERIAL

- PC / ABS

LUMENS/RUNTIME

- HIGH: 200L, 8 hrs. runtime
- LOW: 60L, 40 hrs. runtime
- Green/Red: 12.5 hrs. runtime
- Flashing Mode: Press and hold right switch from any mode to activate white flashing light

WATER RATING

- IP67 Dustproof & Waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 2.48 in (63 mm)
- WIDTH: 1.12 in (28 mm)
- DEPTH: 1.26 in (32 mm)
- WEIGHT: 1.8 oz (51 g)

BATTERY

- LiPo USB-C rechargeable battery
- Recharge Time: 2.75 hrs.

WARRANTY

- 2 year limited warranty

WHAT'S INCLUDED

- Headlamp w/integrated LiPo rechargeable battery
- USB-C charging cord (2')
- Elastic headband
- Integrated brim clip
- 3M® adhesive locking mount (NS-HLM3)
- Instruction manual

CERTIFIED



ID 5012927
ELECTRICAL SAFETY
INTRINSICALLY SAFE
SECURITE INTRINSEQUE

XPR-5552G

Bayco Products, Inc.

640 S. Sanden Blvd., Wylie, TX 75098

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS. Use BAYCO Li-ion Battery Pack 5554-BATT only.

CLASS I DIV 1 GRPS A-D T4
CLASS II & III DIV1 GRPS E-G T180°C
CLASS I ZONE 0 AEx ia IIC T4 Ga
ZONE 20, AEx ia IIC T180°C Da
Ⓢ II 1 G Ex ia IIC T4 Ga
Ⓢ II 1 D Ex ia IIC T180°C Da

Battery Safe Mode (On/Off)

Hold both switches for 3 seconds

Ex ia IIC T4 Ga
Ex ia IIC T180°C Da
IECEx: IECEx ETL 24.0030X
ATEX: ETL24ATEX0415X
ETL25CA105663145X
-10°C ≤ Tamb ≤ +40°C
3.6V/Cell Li-ion
IP-67

CE 2903

ANSI PLATO FL1	WHITE HI	WHITE LO	RED	GREEN
	200 LUMENS	40 LUMENS		
	8h	40h	12.5h	12.5h
	2m			IP67



Includes 3M® VHB
4991 adhesive locking
attachment for band-
free mount (NS-HLM3)