Eaton NON-3/4

Catalog Number: NON-3/4

Eaton Bussmann series NON fuse, Non current limiting, Light duty circuit locations, 0.75 A, Class H, Non-indicating, Ferrule end x ferrule end, 50 kAIC at 125 Vdc|50 kAIC at 250 Vac, Standard, 10, 250 V, 125 Vdc

General specifications

Product Name	Catalog
Eaton Bussmann series NON fuse	NON-3
UPC	EAN
051712300148	50275
Product Length/Depth	Produc
0.56 in	2 in
Product Width	Produc
0.56 in	0.35 lb
Warranty	Compli
Not Applicable	CE Ma

og Number 3/4 590453721 ct Height ct Weight b

liances arked





Electrical rating

Amperage Rating

0.75 A

Interrupt rating

50 kAIC at 125 Vdc 50 kAIC at 250 Vac

Voltage rating

250 Vac, 125 Vdc

Physical details

Packaging type

Standard

General information

Class

Class H

Connection Ferrule end x ferrule end

Fuse indicator

Non-indicating

Quantity

10

Special features

Non current limiting

Resources

Catalogs

NON-3/4~NON-3-4~BUSS ONE TIME FUSE

Bussmann series complete full line catalog no. 1007

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - NON-3/4



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

© 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia