



BURNDY Catalog Number
UPC Number
Description
Status

YA4CL2TC14
 7818105035600
 CULUG-4STR-1/4STD5/8C-C
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle Straight
 Length (in) 2.36
 Barrell Style Chamfered,Skived
 Bolt Hole Size (in) 0.27
 Barrel Type Standard
 Thickness 0.09
 B Length (in) 0.81
 Pad Width (in) 0.50
 E - in 0.62
 Strip Length 7/8

General

Number of Holes 2
 CU Compression Terminal Code
 Conductor, Beveled Entry, 2
 Hole/W/InspWindow,
 #4AWG(Code) 40(Navy), 600V-
 35kV, 1/4" Stud, 0.62 Spacing,
 STRD bbl, Tin - Electro Plated

Product Description

Conductor(s)

Flex (Class G) Size - Range N/A
 Flex (Class H) Size - Range N/A
 Flex (Class I) Size - Range N/A
 Copper Solid Size (Range) N/A
 DLO Size (Range) N/A
 Copper Stranded (Range) 4 AWG

Physical

Type of Plating Tin - Electro Plated
 Bolt Hole Size 1/4
 Color Code Gray
 Plated (Yes or No) Y
 Index Number 8,346
 Product Material Copper

Approvals / Certifications

UL Listed Y
 CSA Certified Y
 ROHS Compatible Compliant
 UL Recognized N
 CULUS N
 Industry Standards UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175