




**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

KVSU44  
 7818100848099  
 UNIV OKLIP 4/0-1000  
 Active

**Web Use**  
 BURNDY Product Line



**General**  
 Tin-plated copper alloy connector with tin plated silicon bronze hardware. Spacer bar separates dissimilar conductors and provides long contact length, Tightening torque: 500 in -lb, wrench size: 5/16 cross flats

Product Description

**Conductor(s)**  
 Aluminum Run Size (Range) 500 kcmil-1000 kcmil  
 Copper Tap Range 4/0 AWG-1000 kcmil  
 CopperWeld Solid Run Size (Range) -  
 Copper Stranded Run (Range) 500 kcmil-1000 kcmil  
 CopperWeld Stranded Tap Size (Range) -  
 CopperWeld Solid Tap Size (Range) -  
 Aluminum Tap Size (Range) 4/0 AWG-1000 kcmil  
 Galvanized Steel Size (Range) 7/8 (19) in-1 1/8 (37) in  
 CopperWeld Stranded Run Size (Range) -

**Approvals / Certifications**  
 UL Listed N  
 CSA Certified Y  
 ROHS Compatible Exempt  
 UL Recognized N  
 CULUS N

**Physical**  
 Installation Torque 500  
 Type of Plating Tin  
 Plated (Yes or No) Y  
 Product Material Copper Alloy

**Documentation**

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175