



## YDS361R

by Burndy  
Catalog ID: YDS361R

Prop 65 Notice

2-piece, full tension ACSR splice consists of steel inner sleeve and AL outer sleeve, Inner Sleeve: 5.25 IN L, Outer Sleeve: 25.63 IN L

## Product Details

### General

Connector Type	Splice
Die Index - Element A	248
Die Index - Element B	327
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Trade Name	HYSPLICE™
UPC	781810821046
UPC 12 Digit	7818108210466

### Dimensions

Dimension - Aluminum Sleeve Length inch	25.625 in
Dimension - B Length fraction	2-1/2 in
Dimension - B Length inch	2.5 in
Dimension - L Length Overall mm	645 mm
Dimension - Length Overall inch	25.38 in
Dimension - Outside Diameter inch	1.3 in
Dimension - Steel Sleeve Length inch	5.25 in

### Conductor Related

Conductor - ACSR Str Size	477.0 (18/1) Pelican kcmil
Conductor - ACSR Str Size Range	477.0 (18/1) Pelican kcmil
Conductor Type	<ul style="list-style-type: none"> <li>• ACSR C Str-Size</li> <li>• AL C Str-Size</li> </ul>

### Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM

UL Listed	No
-----------	----

## Logistics

Minimum Pack Quantity	1
-----------------------	---

### For further technical assistance, please contact us

#### **BURNDY Headquarters**

47 East Industrial Park Drive  
Manchester, New Hampshire 03109

#### **Customer Service Hours:**

8 AM - 8 PM Eastern Monday-Friday  
Emergency Service 24-hours/365 Days  
Phone: 1-800-346-4175  
1-603-647-5299 (International)