




BURNDY Catalog Number
UPC Number
Description
Status

YA32L14
7818100189277
400 CU 1-HOLE SHORT 3/8
Active

Web Use
BURNDY Product Line



Tongue Angle
Length (in)
Tongue Type
Barrell Style
Bolt Hole Size (in)
Barrel Type
Thickness
B Length (in)
Pad Width (in)
Strip Length

Dimensional

Straight
2.68
Standard
Chamfered,Skived
0.39
Standard
0.19
1.19
1.40
1-1/4

Number of Holes

General

1
Cu Tubing Cu Hylug, 1 Hole with
Inspection Window, 400 kcmil
Code, 400 Navy, 600V-35kV, 3/8"
stud, Standard, Compression, 0.40
in BCD, Blue

Product Description

Conductor(s)

Flex (Class G) Size - Range
Flex (Class H) Size - Range
Flex (Class I) Size - Range
Copper Solid Size (Range)
DLO Size (Range)
Copper Stranded (Range)

N/A
N/A
N/A
N/A
N/A
350 kcmil

Type of Plating
Color Code
Plated (Yes or No)
Index Number
Product Material

Physical

Tin - Electro Plated
Blue
Y
19
Copper

Approvals / Certifications

UL Listed
CSA Certified
ROHS Compatible
UL Recognized
CULUS
Industry Standards

Y
Y
Compliant
N
N
UL467

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175