



BURNDY Catalog Number
UPC Number
Description
Status

YA36L2TC38
 7818100209688
 CU HYDENT 600MCM (2)3/8
 Active

Web Use
 BURNDY Product Line

Tongue Angle
 Length (in)
 Tongue Type
 Barrell Style
 Bolt Hole Size (in)
 Barrel Type
 Thickness
 B Length (in)
 Pad Width (in)
 E - in
 Strip Length

Dimensional

Straight
 4.23
 Standard
 Chamfered
 0.39
 Standard
 0.27
 1.38
 1.74
 1.00
 1-3/4

Number of Holes

General

2
 Cu compression tubular terminals-
 code conductor, 2 holes/W/ insp
 window, 600 kcmil, 3/8" stud,
 Green, 22 or 472 index

Product Description

Conductor(s)

Flex (Class G) Size - Range
 Flex (Class H) Size - Range
 Flex (Class I) Size - Range
 Copper Solid Size (Range)
 DLO Size (Range)
 Copper Stranded (Range)

N/A
 N/A
 N/A
 N/A
 N/A
 600 kcmil

Type of Plating
 Color Code
 Plated (Yes or No)
 Index Number
 Product Material

Physical

Tin
 Green
 Y
 22,472
 Copper

Approvals / Certifications

UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS
 Industry Standards

Y
 Y
 Compliant
 N
 N
 UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM

Monday - Friday

Phone: 800-346-4175