



BURNDY Catalog Number
UPC Number

YA38LTC58FX
7818100211188
CUHYLUG 535.3KCMIL 5/8STUD
TEL
Active

Description
Status

Web Use
BURNDY Product Line

Dimensional

Tongue Angle	Straight
Length (in)	3.66
Tongue Type	Standard
Barrell Style	Chamfered
Bolt Hole Size (in)	0.66
Barrel Type	Standard
Thickness	0.27
B Length (in)	1.45
Pad Width (in)	1.84
Strip Length	1-7/16

General

Number of Holes	1
Product Description	Copper Compression Lug, 1 Hole w/ Inspection Window, 500 Flex, 5/8" Stud, Short Barrel, Tin Plated

Conductor(s)

Flex (Class G) Size - Range	500 kcmil
Flex (Class H) Size - Range	500 kcmil
Flex (Class I) Size - Range	500 kcmil
Copper Solid Size (Range)	N/A
DLO Size (Range)	535.3 (1325/#24) DLO
Copper Stranded (Range)	N/A

Physical

Type of Plating	Tin
Bolt Hole Size	5/8
Color Code	Pink
Plated (Yes or No)	Y
Index Number	L99
Product Material	Copper

Approvals / Certifications

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175