



BURNDY Catalog Number
UPC Number
Description
Status

YA36LTC12FX
7818100215144
HYLUG 450 MCM (NOM) FLEX
Active

Web Use
BURNDY Product Line

Tongue Angle
Length (in)
Tongue Type
Barrell Style
Bolt Hole Size (in)
Barrel Type
Thickness
B Length (in)
Pad Width (in)
Strip Length

Dimensional

Straight
3.29
Standard
Chamfered
0.52
Standard
0.27
1.38
1.74
1-3/8

Number of Holes
Product Description

General

1
Copper Compression Lug, 1 Hole
w/ Inspection Window, 450 Flex,
1/2" Stud, Short Barrel, Tin Plated

Flex (Class G) Size - Range
Flex (Class H) Size - Range
Flex (Class I) Size - Range
Copper Solid Size (Range)
DLO Size (Range)
Copper Stranded (Range)

Conductor(s)

450 kcmil
450 kcmil
450 kcmil
N/A
444.4 (1100/#24) DLO
N/A

Type of Plating
Bolt Hole Size
Color Code
Plated (Yes or No)
Index Number
Product Material

Physical

Tin
1/2
Brown
Y
20,299
Copper

UL Listed
CSA Certified
ROHS Compatible
UL Recognized
CULUS

Approvals / Certifications

Y
Y
Compliant
N
N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175