



Main

Product	Double Throw Safety Switch
Current Rating	200 A
Enclosure Rating	NEMA 4/4X/5 Stainless Steel
Factory Installed Neutral	None
Disconnect Type	Non-fusible disconnect
Mounting Type	Surface
Number of Poles	3
Voltage Rating	480 V AC 250 V DC
Wire Size	AWG 6...300 kcmil copper or aluminium

Complementary

Maximum Horse Power Rating	15 hp 480 V AC 50...60 Hz 3 phase NEC 430.52
Width	23.88 in (606.55 mm)
Height	30.88 in (784.35 mm)
Maximum Depth	11.75 in (298.45 mm)
Tightening torque	340 lbf.in (38.41 N.m) AWG 6...300 kcmil

Ordering and shipping details

Category	00066 - MISC H/D SWITCHES
Discount Schedule	DE1
GTIN	00785901017615
Nbr. of units in pkg.	1
Package weight(Lbs)	126 lb(US) (57.15 kg)
Returnability	Yes
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------