

Product availability : Stock - Normally stocked in distribution facility



Price\* : 1380.00 USD



Main

Product or component type	Starter
Range of product	S
Line Rated Current	45 A
Product certifications	CSA NEMA UL listed
Control circuit	Common control circuit
Control type	No control units
NEMA degree of protection	NEMA 12 painted sheet steel
Rated power in HP	7.5 HP 230 V AC 3 HP 115 V AC
Poles description	2P
Phase	1 phase
System Voltage	600 V AC
NEMA size	2
[Uc] control circuit voltage	220 V AC 50 Hz 240 V AC 60 Hz
Motor starter type	Non reversing
Electrical connection	Screw clamp terminals
Thermal overload type	Melting alloy 1

Ordering and shipping details

Category	21192 - 8502,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901019329
Nbr. of units in pkg.	1
Package weight(Lbs)	17.100000000000001
Returnability	N

---

Country of origin	MX
-------------------	----

---

### Offer Sustainability

---

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be compliant on 3Q2014 Will be compliant on 3Q2014
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

---

### Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---