Product data sheet Characteristics

QOB360VH

QO Miniature Circuit Breaker 60A 3P 240V 22kA **Bolt-on Mount**

Product availability: Stock - Normally stocked in distribution facility







Main

The state of the s		:
		•
Main		
Product or component type	Miniature circuit-breaker	 ;
Range of product	QO	-
Line Rated Current	60 A	
System Voltage	240 V AC	
Mounting mode	Bolt-on	
Poles description	3P	
Circuit breaker type	Standard	
Circuit breaker application	HACR rated	
Electrical connection	Box lugs	:
Complementary		,
Breaking capacity	22 kA at: 240 V AC	
Number of spaces required	3	
AWG gauge	AWG 8AWG 2 (copper or aluminium)	
Height	3.12 in	
Depth	2.91 in	
Width	2.25 in	
Environment		
Product certifications	UL listed	
Ambient air temperature for operation	CSA 104 °F (40 °C)	·
Ambient all temperature for operation	104 1 (40 0)	:
Ordering and shipping details		;
Category	00015 - QOB CIRCUIT BREAKERS	
Discount Schedule	DE2	<u>.</u>
Con 20, 2047		

Complementary

Breaking capacity	22 kA at: 240 V AC
Number of spaces required	3
AWG gauge	AWG 8AWG 2 (copper or aluminium)
Height	3.12 in
Depth	2.91 in
Width	2.25 in

Environment

Product certifications	UL listed CSA
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	00015 - QOB CIRCUIT BREAKERS
Discount Schedule	DE2

GTIN	00785901054832
Nbr. of units in pkg.	1
Package weight(Lbs)	1.060000000000001
Returnability	Υ
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period 18 months
