

Certificate of Compliance

Certificate: 1101642 (LR 92886-33) **Master Contract:** 153555

Project: 70196884 **Date Issued:** 2018-09-27

Issued to: Schneider Electric USA, Inc. Square D

3700 6th St SW

Cedar Rapids, Iowa 52404

USA

Attention: Manuel Salinas

The products listed below are eligible to bear the CSA Mark shown



Issued by: Ronald Tateishi

Ronald Tateishi

PRODUCTS

CLASS 1432 01 - CIRCUIT BREAKERS - Moulded Case Type

Circuit breakers, Types QOC and QOCB, common trip, thermal magnetic trip, uncompensated, two-pole, 110 and 125A, 120/240V ac max.

Notes:

- 1. The mechanism is trip-free of the handle, which assumes a mid-position between on and off upon automatic tripping.
- 2. These circuit breakers are suitable for use with copper and aluminum conductors.
- 3. These circuit breakers may be provided with accessories.

DQD 507 Rev. 2016-02-18



 Certificate:
 1101642 (LR 92886-33)
 Master Contract:
 153555

 Project:
 70196884
 Date Issued:
 2018-09-27

4. These circuit breakers may be marked with high-current interrupting ratings in RMS symmetrical amperes, as follows:

<u>Type</u>	Amperes	<u>Volts</u>	Catalogue No	Interrupting rating, RMS Symmetrical Amps
QOC	110, 125	120/240V	QO2110, QO2125	10kA
QOCB	110, 125	120/240V	QOB2110, QOB2125	10kA
QOC	110, 125	120/240V	QO2110VH, QO2125VH	22kA
QOCB	110, 125	120/240V	QOB2110VH, QOB2125VH	H 22kA
QOC	110, 125	120/240V	QOH2110, QOH2125	42kA
QOCB	110, 125	120/240V	QOHB2110, QOHB2125	42kA

APPLICABLE REQUIREMENTS

 $CSA\ Standard\ C22.2\ No.\ 5\ -\ Molded-Case\ Circuit\ Breakers,\ Molded-Case\ Switches\ and\ Circuit-Breaker\ Enclosures$



Supplement to Certificate of Compliance

Certificate: 1101642 (LR 92886-33) **Master Contract:** 153555

The products listed, including the latest revision described below, are eligible to be marked in accordance with the referenced Certificate.

Product Certification History

Project	Date	Description
70196884	2018-09-27	Addition of the use of an alternate arc stack.
1883360	2007-02-14	Addition of alternate material (melamine, Iten MLE 400) for the slide fiber.