

Product availability : Stock - Normally stocked in distribution facility



Price* : 51.00 USD



Main

| | |
|------------------------------|--|
| Range of product | Power Relay 8501C |
| Product or component type | Power relay |
| Device short name | Type C |
| Line Rated Current | 30 A |
| Device application | Suited for controlling small single phase motors and other light loads |
| [Uc] control circuit voltage | 480 V AC at 50/60 Hz |
| Rated power in hp | 1.5 hp |
| Maximum switching voltage | 600 V AC |

Complementary

| | |
|-------------------------------|----------------------|
| Catalog class | 8501 |
| Switch function | DPST |
| Contacts type and composition | 2 NO |
| Mounting support | Panel mounting |
| Phase | 1 phase |
| Connections - terminals | Screw clamp terminal |

Environment

| | |
|---------------------------------------|------------------------|
| Product certifications | CE UL listed CSA |
| Ambient air temperature for operation | -22...122 °F |

Ordering and shipping details

| | |
|-------------------|----------------|
| Category | 21131 - 8501 C |
| Discount Schedule | CP2 |
| GTIN | 00785901059592 |

| | |
|-----------------------|--------------------|
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.5999999999999998 |
| Returnability | Y |
| Country of origin | CN |

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1132 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|