



**TERMINAL LUG DATA ‡**

AMPERES	MAX WIRE	MIN WIRE	TYPE
200	250 KCMIL	#6 AWG	CU/AL

DUAL DIMENSIONS: INCHES  
MILLIMETERS

CATALOG NUMBER	VOLTAGE RATINGS	WIRING DIAG	HORSEPOWER RATINGS														
			240VAC				480VAC				600VAC				250 VDC	600 VDC	
			STD		MAX		STD		MAX		STD		MAX		STD	STD	
			1Ø	3Ø	1Ø	3Ø	1Ø	3Ø	1Ø	3Ø	1Ø	3Ø	1Ø	3Ø			
H224DS	240VAC;250VDC	A	15	25&	-	60&	-	-	-	-	-	-	-	-	-	40^	-
H324DS	240VAC;250VDC	B	15^	25&	-	60&	-	-	-	-	-	-	-	-	-	40^	-
H364DS	600VAC;600VDC	B	15^	25&	-	60&	25^	50&	50^	125&	30^	60	50^	150	40^	50^	
H364NDS	600VAC;600VDC	C	15^	25#	-	60#	25^	50#	50^	125#	30^	60	50^	150	40^	60^	
HU3B4DS	600VAC;600VDC	D	-	-	15^	60&	-	-	80^	125&	-	-	50^	150	40^	<	50^

NOTES:  
 FINISH - TYPE 304 STAINLESS STEEL  
 UL LISTED - E2875  
 NEUTRALS - INSULATED GROUNDABLE  
 SUITABLE FOR USE AS SERVICE EQUIPMENT  
 SHORT CIRCUIT CURRENT RATINGS:  
 10,000 AMPERES WHEN USED WITH OR PROTECTED BY CLASS H OR K FUSES,  
 200,000 AMPERES WHEN USED WITH OR PROTECTED BY CLASS R OR J FUSES,  
 ON 600V SWITCHES, 100,000 AMPERES MAX ON CORNER GROUNDED DELTA WHEN PROTECTED BY  
 BY CLASS J OR R FUSES, 200 AMPERE MAX.  
 ‡ LUGS SUITABLE FOR 75°C CONDUCTORS.  
 # IF CORNER GROUNDED DELTA, USE OUTER SWITCHING POLES FOR UNGROUNDED CONDUCTORS.  
 \* IF CORNER GROUNDED DELTA, INSTALL NEUTRAL AND USE OUTER SWITCHING POLES FOR UNGROUNDED CONDUCTORS.  
 & USE ANY TWO SWITCHING POLES.  
 < MAX RATING

**HEAVY DUTY SAFETY SWITCHES**  
 VISIBLE BLADE TYPE  
 200 AMPERE - SERIES F6  
 ENCLDURE - NEMA 4, 4X AND 5 STAINLESS STEEL



DWG# 3232  
 NO.