

Eaton FWP-15A14F

Catalog Number: FWP-15A14F

Eaton Bussmann series FWP high speed fuse, 700 Vac (UL), 700 Vdc (UL), 690 Vac (IEC), 15, 200 kAIC at 700 Vac, 50 kAIC at 700 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end, Class aR, White, Ceramic



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed cylindrical fuse	FWP-15A14F
	UPC
	051712795937
EAN	Product Length/Depth
5027590500210	51 mm
Product Height	Product Width
15 mm	15 mm
Product Weight	Warranty
20.4 g	Not Applicable
Compliances	Certifications
CE Marked	UL Recognized
RoHS Compliant	CSA Certified

Product specifications

Interrupt rating

200 kAIC

Release characteristic

Other

Amperage Rating

15 A

Frequency rating - max

62 Hz

Fuse type

FWP-A14F

Accessories

CH14 Modular fuse holder

FW14-PCB

Minimum melting

8.6 I2t (A2 sec)

Fuse size

14 x 51 mm

Voltage rating

700 V

Fuse indicator

Non Indicating

Construction size

14 mm x 51 mm

Clearing (I2T)

70

Color

White

Connection

Ferrule end x ferrule end

Quantity

10

Material

Ceramic

Utilization category

aR (accompanied semiconductor protection)

Resources

Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc](#)

[UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc](#)

Technical data sheets

[720025 FWP](#)

Watt losses

5.5 W

Type

High speed fuse

Fuse shape

Cylindrical

Used with

Finger safe holders/blocks and striker

Breaking capacity

200 kA

Frequency rating - min

45 Hz

Class

Class aR

Pre arc (I₂T)

10

Application

Semiconductor, DC Common bus, DC drives, Power
converters/rectifiers

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia