

## Certification Record

Customer	Class	File Number
Schneider Electric USA, Inc. Square D Automation and Control Business, 8001 Knightdale Blvd Raleigh NC USA 27545	<u>3211-04</u> INDUSTRIAL CONTROL EQUIPMENT-Motor Controllers - Magnetic	218139

- Contactors, Cat Nos 8501CO or 8501CDO with alphanumeric suffixes, open type, 1 or 2-poles rated:

### Single Make/Break Relays

### Double Make/Break Relays

Contact Material Voltage	Single Make/Break Relays			Double Make/Break Relays		
	Silver Cadmium Oxide	Fine Silver	Tungsten Against SCO	Silver Cadmium Oxide	Fine Silver	Tungsten Against SCO
0-300V ac	-	-	-	50A	50A	-
0-300V ac	30A	30A	20A	30A	30A	20A
480V ac	5A	5A	5A	12A	12A	12A
600V ac	5A	5A	5A	10A	10A	10A
120- 600V ac	1-1/2 hp	-	1 hp	2 hp	-	-
120V	-	-	-	-	1-1/2	-

ac						hp	
200-600V ac	-	1-1/2 hp	-	-	-	2 hp	-
150V ac	-	-	-	-	-	-	1 hp
151-600V ac	-	-	-	-	-	-	1-1/2 hp
120V ac tung.	15A	10A	15A	15A	15A	10A	15A
120-600V ac	960VA	-	768VA	1152A	-	-	-
120V ac	-	-	-	-	-	960VA	-
200-600V ac	-	960VA	-	-	-	1152VA	-
150V ac	-	-	-	-	-	-	768VA
151-600V ac	-	-	-	-	-	-	960VA
0-28V dc	30A	30A	20A	30A	30A	30A	20A
0-28V dc	-	-	-	50A	50A	50A	-

Double-Pole Relays With Both Poles Switching the Load (All other ratings are per pole)

200-	1152VA	1152VA	-	-	-	-	-
------	--------	--------	---	---	---	---	---

600V  
ac

200-  
600V  
ac

2 hp

2 hp

-

-

-

-

All Models When Provided With Blowout Magnets

110V dc

10A

10A

10A

20A

20A

20A

144V  
dc

-

-

-

15A

15A

15A

220V  
dc

4A

4A

4A

10A

10A

10A

325V  
dc

2A

2A

2A

4A

4A

4A

500V  
dc

-

-

-

2A

2A

2A

Coils 0-600V ac or dc.

Notes:

- 1. 50A contactors are provided with CSA Certified pressure wire connectors.
- 2. Contacts with silver cadmium contacts may be marked with A600.