



Main

Product	Receptacle Switch
For Use With	Plug APJ3485 Crouse-Hinds Arktite
Disconnect Type	Fusible disconnect switch
Phase	3 phase
Number of Poles	3
Current rating	30 A
Voltage Rating	600 V AC 250 V DC
Enclosure Rating NEMA 3R	NEMA 12K
Maximum Horse Power Rating	5 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 15 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 7.5 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 20 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 5 hp 250 V at DC conforming to NEC 240.6

Complementary

Short-circuit Current Rating	10 KA H or K	
· ·	200 kA R or J	
Fuse Type	H or K	
•	R or J	
Mounting Type	Surface	
Electrical Connection	Receptacle	
Wire Configuration	4-wire	
Wire Size	AWG 12AWG 2 aluminium	
	AWG 14AWG 2 copper	
Tightening torque	45 Lbf.In (5.08 N.m) (AWG 6)	
	40 Lbf.In (4.52 N.m) (AWG 8)	
	35 lbf.in (3.95 N.m) (AWG 14AWG 10)	
Depth	7 in (177.80 mm)	
Width	10.5 in (266.70 mm)	
Height	16.5 in (419.10 mm)	
Net weight	28.66 lb(US) (13 kg)	

Environment

Certifications UL Listed	Certifications	
--------------------------	----------------	--

Ordering and shipping details

00118 - H&HU SW,W/C-HINDS RECPT-WC	
DE1	
00785901076971	
1	
23.00 lb(US) (10.433 kg)	
Yes	
US	
	DE1 00785901076971 1 23.00 lb(US) (10.433 kg) Yes

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.40 in (18.796 cm)
Package 1 width	11.00 in (27.94 cm)
Package 1 Length	25.90 in (65.786 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	€ Yes
China RoHS Regulation	[™] China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Contractual warranty		
Warranty	18 months	