



IZLT.E40747 Fuseholders, Cartridge Fuse

If you notice a change to your IZLT Listing Card, click [here](#) to learn more.

[Page Bottom](#)

Fuseholders, Cartridge Fuse

See General Information for Fuseholders, Cartridge Fuse

SCHNEIDER ELECTRIC USA, INC.

8001 KNIGHTDALE BLVD
KNIGHTDALE, NC 27545-9023 USA

E40747

Cat. No.	Voltage Rating (V)	Current Rating (A)	Withstand Rating RMS Symmetrical	Fuse Class or Size
FB1211	250ac/dc	30	100000	H
FB1211R,	600ac/dc	30	200000	R
FB1221	250ac/dc	30	100000	H
	600ac/dc	60	100000	H
FB1221C	250ac/dc	30	100000	H
	600ac/dc	60	100000	H
FB1221R	600ac/dc	30	200000	R
FB1231C	250ac	100	100000	H or R
	600ac	100	200000	H or R
FB1231R	600ac/dc	30	200000	R
FB1241	250ac/dc	200	100000	H or K
FB1241C	600ac/dc	200	100000	H or K
FB1241R	600ac/dc	30	200000	R
FB1251	600ac/dc	200	100000	H or K
FB1251R	600ac/dc	30	200000	R
FB1611	250ac	30	100000	H
	600ac	60	100000	H
FB1611CC	600ac/dc	30	200000	CC
FB1611J	600ac	30	200000	J
	600ac	60	200000	J
FB1611R	600ac/dc	30	200000	R
FB1621C	600ac	60	100000	H
	250ac	30	100000	H
FB1621J	600ac	60	200000	J
	600ac	30	200000	J
FB1621R	600ac/dc	30	200000	R
FB1631	250ac	100	100000	H or R
	600ac	100	200000	H or R
FB1631C	250ac/dc	100	100000	H or K
	600ac/dc	100	100000	H or K

FB1631R	600ac/dc	30	200000	R
FB1641	600ac/dc	200	100000	H or K
FB1641C	600ac/dc	200	100000	H or K
FB1641R	600ac/dc	30	200000	R
FB1651	600ac/dc	30	200000	R
FB1651R	600ac/dc	30	200000	R
FB2211	250ac/dc	30	100000	H
FB2211R	600ac/dc	30	200000	R
FB2221	250ac/dc	30	100000	H
	600ac/dc	60	100000	H
FB2221C	600ac/dc	60	100000	H
	250ac/dc	30	100000	H
FB2221R	600ac/dc	30	200000	R
FB2231	250ac	30	100000	H
	600ac	60	200000	H
FB2231C	600ac	100	200000	H or R
	250ac	100	100000	H or R
FB2231R	600ac/dc	30	200000	R
FB2611	600ac	60	100000	H
	250ac	30	100000	H
FB2611CC	600ac/dc	30	200000	CC
FB2611J	600ac	30	200000	J
	600ac	60	200000	J
FB2611R	600ac/dc	30	200000	R
FB2621	250ac	30	100000	H
	600ac	60	100000	H
FB2621C	600ac	60	100000	H
	250ac	30	100000	H
FB2621J1	600ac	30	200000	J
	600ac	60	200000	J
FB2621R	600ac/dc	30	200000	R
FB2631	250ac	100	100000	H or R
	600ac	100	200000	H or R
FB2631C	600ac/dc	100	100000	H or K
	250ac/dc	100	100000	H or K
FB2631R	600ac/dc	30	200000	R
FB3211	250ac/dc	30	100000	H
FB3211R	250ac/dc	30	200000	R
FB3221	600ac/dc	60	100000	H
	250ac/dc	30	100000	H
FB3221C	600ac/dc	60	100000	H
	250ac/dc	30	100000	H
FB3221R	250ac/dc	60	200000	R
FB3231	600ac	200	100000	H

FB3231C	600ac	100	200000	H or R
	250ac	100	100000	H or R
FB3231R	600ac/dc	30	200000	R
FB3241	600ac/dc	200	100000	H or K
FB3241C	600ac/dc	200	100000	H or K
FB3241R	600ac/dc	30	200000	R
FB3251	600ac/dc	400	100000	R
FB3251R	600ac/dc	30	200000	R
FB3611	600ac	60	100000	H
	250ac	30	100000	H
FB3611CC	600ac/dc	30	200000	CC
FB3611J	600ac	30	200000	J
	600ac	60	200000	J
FB3611R	600ac/dc	30	200000	R
FB3621	250ac	30	100000	H
	600ac	60	100000	H
FB3621C	250ac	30	100000	H
	600ac	60	100000	H
FB3621J	600ac	30	200000	J
	600ac	60	200000	J
FB3621R	600ac/dc	30	200000	R
FB3631	600ac	100	200000	H or R
	250ac	100	100000	H or R
FB3631C	600ac/dc	100	100000	H or K
	250ac/dc	100	100000	H or K
FB3631R	600ac/dc	30	200000	R
FB3631RC	250ac	100	100000	H or R
	600ac	100	200000	H or R
FB3641	600ac/dc	200	100000	H or K
FB3641C	600ac/dc	200	100000	H or K
FB3651	600ac/dc	30	200000	R
FB3651R	600ac/dc	30	200000	R
PF-1	250ac	30	100000	H
	600ac	60	100000	H
PFR-1	600ac/dc	30	200000	R

Last Updated on 2017-04-05

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with

permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".