



Product Datasheet



ANDERSON FARGO

VAUS4040 -- Minimum Tension Splice



Minimum tension aluminum splice for copper, AAC and ACSR

Product Specifications

<p>Splice Type</p>	 <p>VERSAtile™ Compression Splices (For use with Die type and VersaCrimp tools)</p>
<p>Versatile Compression Series</p>	 <p>VACS Series Compression Splice VERSAtile™ Minimum Tension Aluminum or Copper Conductor</p>
<p>PDF Catalog Page</p>	<p>Click HERE to view the web page.</p>
<p>Conventional Tooling Minimum Conductor - End A</p>	<p>0.522 in</p>
<p>Conventional Tooling Maximum Conductor - End A</p>	<p>0.575 in</p>
<p>Conventional Tooling Minimum Conductor - End B</p>	<p>0.522 in</p>
<p>Conventional Tooling Maximum Conductor - End B</p>	<p>0.575 in</p>
<p>VersaCrimp Tooling Minimum Conductor - End A</p>	<p>0.204 in</p>
<p>VersaCrimp Tooling Maximum Conductor - End A</p>	<p>0.575 in</p>
<p>VersaCrimp Tooling Minimum Conductor - End B</p>	<p>0.204 in</p>
<p>VersaCrimp Tooling Maximum Conductor - End B</p>	<p>0.575 in</p>
<p>Material</p>	<p>Aluminum</p>
<p>Conventional Tooling Range End A</p>	<p>4/0-250 Str. Al/Cu 4/0 ACSR 250-300 Comp.</p>
<p>Conventional Tooling Range End B</p>	<p>4/0-250 Str. Al/Cu 4/0 ACSR 250-300 Comp.</p>

VersaCrimp Conductor Minimum - End A	.204 in
VersaCrimp Conductor Maximum - End A	.575 in
VersaCrimp Conductor Range End A	#4 Sol. -250 Str. Al/Cu & #5-4/0 ACSR
VersaCrimp Conductor Minimum - End B	.204 in
VersaCrimp Conductor Maximum - End B	.575 in
VersaCrimp Conductor Range End B	#4 Sol. -250 Str. Al/Cu & #5-4/0 ACSR
Outside Diameter	0.906 in
Dimension D	1.88 in (48 mm)
Dimension L	4.00 in (102 mm mm)
Length before Compression	4.00 in (102 mm)
Compression Method	VersaCrimp or Conventional Die Tooling
Die Size	840
Cover Available	No
Color Code	Pink
Material Type	Non-Standard
UPC Code	09635933528
Standard Package	25
Standard Package Unit	Each
Min Order Qty	25
Weight / Ea.	0.196 lbs

Notes

For use with either VersaCrimp or conventional tooling (not for copper to copper connections) factory loaded with non-petroleum sealant.

Features

Entire VAUS series installs with only 4 common die sizes|color coded end caps through 4/0.

Compressed Product Number

VAUS4040

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.