

Actual

Catalog Number: 40CA

 Product ID:
 7TAH006150R0003

 UPC Number:
 78378620058

 EAN Number:
 05414363142157

Status: Active

Type CA Aluminum Split-Bolt Connector with Spacer and Washer for Use on Copper, Aluminum Conductors. Conductor Range for Equal Main and Tap 4/0 Str.-2/0 Sol.

- Bolt, nut, pressure bar and contoured spacer of aluminum alloy. Pressure bar and contoured spacer made of electrolytic copper. Spacer is completely tin plated.
- Bolt and nut are anodized to prevent seizing of threads and reduce galvanic corrosion when in contact with copper conductor.
- Splicing, tapping or terminating conductors in power and grounding electrical connection

North American Specifications (UNSPSC)	
UNSPSC	39121408 Mechanical connectors
IGCC	4541 Mechanical connectors
Brand Name	Blackburn
Туре	Split-Bolt
Special Features	Bolt, nut, pressure bar and contoured spacer of alu- minum alloy. Pressure bar and contoured spacer made of electrolytic copper. Spacer is completely tin plated.
Application	Splicing, tapping or terminating conductors in power and grounding electrical connection.
Standard	UL E9809
Material	Aluminum
Color	Metallic

European Specifications	(ETIM)
ETIM	EC000491 Earth terminal clamp
Suitable for	Round conductor
Material	Copper
Packaging	
Inner Quantity	25
Inner Dimensions (inches)	7x5.3x6.3
Outer Quantity	150

5.2x4.7x3

30 lbs. per 100

Documents / Support Tools

Outer Dimensions (inches)

Weight Uom

Technical Drawing / Data Sheet US Available on Website

For further technical assistance, please contact us...

ABB Installation Products Technical Support MS 3B-50

860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday

Phone: (888) 862-3289 Fax: (901) 252-1321

Email:techsupport@tnb.com

ABB Installation Products - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com