

SAFETY DATA SHEET



SDS-00055 [T & B CONTAX AN-2]

Section 1. Identification

GHS product identifier : SDS-00055 [T & B CONTAX AN-2]
Product code : See Section 16
Other means of identification : Not available.
Product type : Solid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Corrosion inhibitor.
Area of application : Consumer applications.

Manufacturer : ABB Installation Products Inc.
860 Ridge Lake Blvd.
Memphis, TN 38120, US

Telephone no.: 1-888-862-3289

Emergency telephone number (with hours of operation) : INFOTRAC – 24 Hours 1-800-535-5053
+1 352-323-3500 (Outside USA)

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture : H317 SKIN SENSITIZATION - Category 1
H351 CARCINOGENICITY - Category 2
H372 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H317 - May cause an allergic skin reaction.
H351 - Suspected of causing cancer.
H372 - Causes damage to organs through prolonged or repeated exposure. (lungs, respiratory tract)

Precautionary statements

Section 2. Hazards identification

Prevention	: P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P280 - Wear protective gloves, protective clothing and eye or face protection. P260 - Do not breathe dust. P270 - Do not eat, drink or smoke when using this product. P264 - Wash thoroughly after handling.
Response	: P308 + P313 - IF exposed or concerned: Get medical advice or attention. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P362 + P364 - Take off contaminated clothing and wash it before reuse.
Storage	: P405 - Store locked up.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Avoid contact with skin and clothing. Wash thoroughly after handling.
Hazards not otherwise classified	: Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

Ingredient name	Other names	%	Identifiers
nickel	-	≥10 - ≤15	CAS: 7440-02-0
Aluminium powder (pyrophoric)	-	≥10 - ≤15	CAS: 7429-90-5

Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Section 4. First aid measures

Ingestion : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.
Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : Adverse symptoms may include the following:
 irritation
 redness
 dryness
 cracking
Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments : No specific treatment.
Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical or CO₂. Foam
Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical : No specific fire or explosion hazard.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
 metal oxide/oxides
 carbon oxides

Section 5. Fire-fighting measures

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities	: Keep away from children. Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.
---	--

Section 8. Exposure controls/personal protection

Occupational exposure limits

Ingredient name	Exposure limits
nickel	ACGIH TLV (United States, 1/2025) A5. TWA 8 hours: 1.5 mg/m³. Form: Inhalable fraction. NIOSH REL (United States, 10/2020) [nickel metal and other compounds] NIA. TWA 10 hours: 0.015 mg/m³ (as Ni). OSHA PEL (United States, 5/2018) [Nickel, metal and insoluble compounds] TWA 8 hours: 1 mg/m³ (as Ni). CAL OSHA PEL (United States, 1/2025) TWA 8 hours: 0.5 mg/m³ (as Ni).
Aluminium powder (pyrophoric)	ACGIH TLV (United States, 1/2025) [Aluminum, metal and insoluble compounds] A4. TWA 8 hours: 1 mg/m³. Form: Respirable fraction. NIOSH REL (United States, 10/2020) TWA 10 hours: 10 mg/m³. Form: Total. TWA 10 hours: 5 mg/m³. Form: Respirable fraction. OSHA PEL (United States, 5/2018) TWA 8 hours: 15 mg/m³ (as Al). Form: Total dust. TWA 8 hours: 5 mg/m³ (as Al). Form: Respirable fraction. CAL OSHA PEL (United States, 1/2025) TWA 8 hours: 5 mg/m³. Form: powder.

Biological exposure indices

Ingredient name	Exposure indices
nickel	ACGIH BEI (United States, 1/2025) [nickel and inorganic compounds] BEI: 30 µg/l, nickel [in urine after exposure to soluble compounds]. Sampling time: post-shift at end of workweek. BEI: 5 µg/l, nickel [in urine after exposure to elemental nickel and poorly soluble compounds]. Sampling time: post-shift at end of workweek.

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Section 8. Exposure controls/personal protection

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state : Solid. [Paste./Thick grease]
Color : Gray.
Odor : Not available.
Odor threshold : Not available.
pH : Not available.
Melting point/freezing point : Not available.
Boiling point or initial boiling point and boiling range : Not available.
Flash point : Closed cup: >200°C (>392°F)
Evaporation rate : Not available.
Flammability : Not Flammable

Section 9. Physical and chemical properties

Lower and upper explosion limit/flammability limit	: Not applicable.
Vapor pressure	: Not applicable.
Relative vapor density	: Not applicable.
Relative density	: Not available.
Density	: Not available.
Solubility(ies)	: Not available.
Partition coefficient: n-octanol/water	: Not applicable.
Auto-ignition temperature	: Not applicable.
Decomposition temperature	: Not available.
SADT	: Not available.
Viscosity	: Dynamic (room temperature): Not applicable. Kinematic (room temperature): Not applicable. Kinematic (40°C (104°F)): Not applicable.

Particle characteristics

Median particle size : Not available.

Other information

Physical/chemical properties comments : No additional information.

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerization will not occur.
Conditions to avoid	: Avoid excessive heat.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result
nickel	Rat - Oral - LD50 >2000 mg/kg

Conclusion/Summary [Product] : Not available.

Section 11. Toxicological information

Skin corrosion/irritation

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Conclusion/Summary [Product] : Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
nickel	-	2B	Reasonably anticipated to be a human carcinogen.

Reproductive toxicity

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Result
-------------------------	--------

Section 11. Toxicological information

nickel	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (respiratory tract) (inhalation) - Category 1
Aluminium powder (pyrophoric)	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (lungs) - Category 2

Aspiration hazard

Not available.

Information on the likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness dryness cracking
Ingestion	: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Long term exposure

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Potential chronic health effects

Conclusion/Summary [Product] : Not available.

General : Causes damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Section 11. Toxicological information

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral(mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
SDS-00055 [T & B CONTAX AN-2] nickel	14166.7 2500	N/A N/A	N/A N/A	N/A N/A	N/A N/A

Section 12. Ecological information

Toxicity

Product/ingredient name

nickel

Result

Acute - EC50 - Fresh water

Effect: Growth

Aquatic plants - Duckweed - *Lemna minor*

450 µg/l [4 days]

Chronic - NOEC - Marine water

Effect: Population

Algae - Dinoflagellate - *Glenodinium halli*

100 mg/l [72 hours]

Chronic - NOEC - Fresh water

Effect: Accumulation

Fish - common carp - *Cyprinus carpio*

Age: 13 months; Size: 10.5 cm; Weight:

27.8 g

3.5 µg/l [4 weeks]

Acute - LC50 - Fresh water

Effect: Mortality

Crustaceans - Water flea -

US EPA, OECD

Ceriodaphnia dubia - Juvenile

(Fledgling, Hatchling, Weanling)

Age: 2 to 8 hours

34.6 µg/l [48 hours]

Chronic - EC10

Effect: Reproduction

Daphnia - Water flea - *Daphnia magna* -

OECD

Neonate

Age: <24 hours

6.9 µg/l [21 days]

Acute - LC50 - Fresh water

Effect: Mortality

Fish - Indian catfish - *Heteropneustes*

fossilis

47.5 ng/l [96 hours]

Aluminium powder (pyrophoric)

Acute - LC50 - Fresh water

Effect: Mortality

Fish - Rainbow trout, donaldson trout -

Oncorhynchus mykiss - Embryo

120 µg/l [96 hours]

Chronic - NOEC - Fresh water

Effect: Enzymes

Aquatic plants - Coontail -

Ceratophyllum demersum

Weight: 3.5 g

9 mg/l [3 days]

Section 12. Ecological information

Acute - LC50 - Fresh water

Daphnia - Water flea - *Daphnia magna*
38 mg/l [48 hours]

Effect: Mortality

Conclusion/Summary [Product] : Not available.

Persistence and degradability

Conclusion/Summary [Product] : Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/Water partition coefficient : Not available.

Other adverse effects

May cause long-term adverse effects in the aquatic environment.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	IMDG	IATA
UN number	Not regulated.	UN3077	UN3077
UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (nickel, Aluminium powder (pyrophoric))	Environmentally hazardous substance, solid, n.o.s. (nickel, Aluminium powder (pyrophoric))
Transport hazard class(es)	-	9  	9  
Packing group	-	III	III

Section 14. Transport information

Environmental hazards	No.	Yes.	Yes.
-----------------------	-----	------	------

Additional information

- DOT Classification** : **Reportable quantity** 666.67 lbs / 302.67 kg. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.
- IMDG** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
Emergency schedules F-A, S-F
Special provisions 274, 335, 375, 966, 967, 969
IMDG Code Segregation group SGG15 - Powdered metals
- IATA** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
Quantity limitation Passenger and Cargo Aircraft: 400 kg. Packaging instructions: 956. Cargo Aircraft Only: 400 kg. Packaging instructions: 956. Limited Quantities - Passenger Aircraft: 30 kg. Packaging instructions: Y956.
Special provisions A97, A158, A179, A197, A215
- Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not available.

Section 15. Regulatory information

- U.S. Federal regulations** : **TSCA 8(a) CDR Exempt/Partial exemption:** Not determined
United States inventory (TSCA 8b): All components are active or exempted.
Clean Water Act (CWA) 307: nickel

TSCA 12(b) - Chemical export notification

Not applicable.

- Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)** : Listed
- Clean Air Act Section 602 Class I Substances** : Not listed
- Clean Air Act Section 602 Class II Substances** : Not listed
- DEA List I Chemicals (Precursor Chemicals)** : Not listed
- DEA List II Chemicals (Essential Chemicals)** : Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

- SARA 304 RQ** : Not applicable.

Section 15. Regulatory information

SARA 311/312

Classification : SKIN SENSITIZATION - Category 1
 CARCINOGENICITY - Category 2
 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
 HNOC - Defatting irritant

Composition/information on ingredients

Name	%	Classification
nickel	≥10 - ≤15	SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
Aluminium powder (pyrophoric)	≥10 - ≤15	PYROPHORIC SOLIDS - Category 1 SUBSTANCES AND MIXTURES, WHICH IN CONTACT WITH WATER, EMIT FLAMMABLE GASES - Category 2 COMBUSTIBLE DUSTS SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

SARA 313

	Product name	CAS number	%
Form R-Reporting requirements	nickel	7440-02-0	≥10 - ≤15
	Aluminium powder (pyrophoric)	7429-90-5	≥10 - ≤15
Supplier notification	nickel	7440-02-0	≥10 - ≤15
	Aluminium powder (pyrophoric)	7429-90-5	≥10 - ≤15

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: NICKEL; ALUMINUM
New York : The following components are listed: Nickel
New Jersey : The following components are listed: NICKEL; ALUMINUM
Pennsylvania : The following components are listed: NICKEL CATALYST; ALUMINUM PYRO POWDERS

California Prop. 65

 **WARNING:** This product can expose you to Nickel, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Nickel	-	-

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Section 15. Regulatory information

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Section 16. Other information

Other special considerations : Product codes:

PAE335-79, PAE2121-79, PAE2121-9, PAE2121-9-B1-5, PAE2121X-79, PAE2121X-79,
PAE2-335-79, PAE3921-79-2, PAE3921-79-2SCE, PAE3921-9-2, PAE3921-9-2-P,
PAE3931-9-2, PAE3931-9-2-P, PAE3939-79-2, PAE3939-79-3B, PAE3939-9-2,
PAE4141-79, PAE4141-9, PAE4141-9-B1-5, PAE4141-9P, PAE4141-9-P-7,
PAE9921-79, PAE9921-79SCE, PAE9921-9, PAE9921-9P, PAE9939-79,
PAE9939-79SCE, PAE9939-9, PAE9939-9P, PAE9941-9, PAE9999-79, PAE9999-9

Hazardous Material Information System (U.S.A.)

Health	*	3
Flammability		1
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



Procedure used to derive the classification

Classification	Justification
SKIN SENSITIZATION - Category 1	Calculation method
CARCINOGENICITY - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1	Calculation method

History

Date of issue/Date of revision	: 11/02/2025
Date of previous issue	: No previous validation
Version	: 1
Prepared by	: Sphera Solutions
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods IMO = International Maritime Organization LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group TDG = Transportation of

Section 16. Other information

Dangerous GoodsUN = United Nations

References : HCS (U.S.A.) - Hazard Communication StandardInternational transport regulations

Indicates information that has changed from previously issued version.

Notice to reader

ABB Installation Products Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.