



Representative

**Catalog Number:** RCJ40-BB  
**Product ID:** 7TAA267170R0017  
**UPC Number:** 78378605143  
**Status:** Active

Aluminum 6-3/4 inch Partial-Tension Distribution Compression Splice for Wire Range: 4/0 ACSR(6/1), 4/0 AAAC(7), 4/0 5005(7), 4/0 AAC(7), Hydraulic Dies: B61EA, 654, 1.00

- Meets the 40 Percent Partial Tension Requirement of C119.4

### North American Specifications (UNSPSC)

UNSPSC	39121449 Wire or cable compression splice
IGCC	4669 Wire or cable compression splice
Brand Name	Blackburn
Type	Compression Connector / Splice
Special Features	Type RJC Aluminum Jumper Sleeve for ACSR, AAAC, 5005 and AAC Conductor
Application	Distribution Compression Connector
Standard	ANSI C119.4 - meets the 40 percent partial tension requirement.
Size	6-3/4 inch
Connection	Compression
Conductor Range	Wire Range: 4/0 ACSR(6/1), 4/0 AAAC(7), 4/0 5005(7), 4/0 AAC(7),
Number Of Conductors	2
Material	Aluminum
Insulation	None
Mounting	None

### Packaging

Outer Quantity	25
Outer Dimensions (inches)	10.3x7x4.5
Weight Uom	38 lbs. per 100

### Documents / Support Tools

Technical Drawing / Data Sheet US	Available on Website
-----------------------------------	----------------------

**For further technical assistance, please contact us...**

ABB Installation Products - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

ABB Installation Products Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)