

Catalog Number: RC40

 Product ID:
 7TAA267310R0009

 UPC Number:
 78378605123

Status: Active

Aluminum 18-1/2 inch Full-Tension Distribution Compression Splice for Wire Range: 4/0 AC-SR(6/1), 4/0 AAAC(7), 4/0 5005(7), 4/0 AAC(7), Hydraulic Dies: B61EA, 654, 1.00, 1-2

- Center Stop Accures Proper Conductor Positioning
- External End Taper Provides Conductor Stress Relief, Ease of Stringing and Corona Protection
- Internal End Chamfer Allows Easy Conductor Insertion and Prevents Sharp Edge Contact with Conductor

 Tested to Meet Electrical and Mechanical Requirements of ANSI C119.4, Will withstand 95 Percent of Conductor Rated Breaking Strength

Representative
----------------

North American Specific	ations (UNSPSC)
UNSPSC	39121449 Wire or cable compression splice
IGCC	4669 Wire or cable compression splice
Brand Name	Blackburn
Туре	Compression Connector / Splice
Special Features	Center stop assures proper conductor positioning.
	External end taper provides conductor stress re-
	lief, ease of stringing and corona protection. Interna
	end chamfer allows easy conductor insertion and
	prevents sharp edge contact with conductor. Re-
	places two-piece splices. Type RC Single Sleeve,
	Full Tension Splice for ACSR, AAAC, 5005 and
	AAC Conductor.
Application	Distribution Compression Connector
Standard	ANSI C119.4
Size	18-1/2 inch
Connection	Compression
Conductor Range	Wire Range: 4/0 ACSR(6/1), 4/0 AAAC(7), 4/0
	5005(7), 4/0 AAC(7)
Number Of Conductors	2
Material	Aluminum
Insulation	None
Mounting	None
Packaging	

Packaging	
Outer Quantity	20
Outer Dimensions (inches)	20x6.2x5.5
Weight Uom	119 lbs. per 100

<b>Documents / Support Tools</b>	
Technical Drawing / Data Sheet US	Available on Website
Safety Data Sheet (SDS) Global	SDS-00054-TB2

## For further technical assistance, please contact us...

ABB Installation Products - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com ABB Installation Products Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com