

Catalog Number: Item Description: UPC Code: U1527-XL 200A 4T RL OU 784572134133

Brand Name:	Milbank
Туре:	Ringless Meter Socket
Application:	Meter Socket
Standard:	UL Listed
Voltage Rating:	600 Volts Alternating Current
Amperage Rating:	200 Continuous Ampere
Phase:	1 Phase
Frequency Rating:	60 Hertz
Number Of Cutouts:	0
Cable Entry:	Overhead and Underground
Terminal:	Single Lay in Line Side and Load Side Connectors
Mounting:	Surface Mount
Enclosure:	Type 3R, G90 Galvanized Steel with Powder Coat Finish




Additional Specifications:


Number of Jaws:4 Terminal


Hub Opening and Closing Plates:Small Closing Plate

Utility requirements may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must always be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.

FEATURE TABLE			FEATURE TABLE
	ITEM	QTY	DESCRIPTION
	Α	6	U/L MNTG.EMBOSS
	В	1	1/4 SOLID K.O.
	С	1	1/4, 1/2 CONC. K.O.
	D	5	1, 1¼, 1½, 2 CONC. K.O.
	Е	1	1, 1¼, 1½, 2, 2½ CONC. K.O.









Version:

All dimensions are +/- 1/16". Drawing views are not to scale.

Utility requirements for this equipment may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.