



Residential/Construction, Power Outlets & Temporary Power

Product #: U058C

Short Description: 80A SURFACE UNMTRD 50/30

SPECIFICATIONS

OI LOII IOAT IOIG	
Category	Pow er Outlets & Temporary Pow er
Mounting	Surface
Heads	1
Metering	Unmetered
Receptacles	14-50R, R32U
Feed	Overhead
AIC	10,000
Amps	80.0
Cabinet Size	6 X 14
Circuit Protection	Yes
Hub Provision	Yes
Installed Breaker	CB250, CB130
Load Center	LC33N1
Loop Feed	No
Phase	1
Suitable for Service Equipment	Yes
Standard Package	1
Stock Class Code	Non Stock
Certification	UL/CUL
Unit Weight	15.0
UPC	078456757080
Volts	120/240

Photo Not Available

Photo Not Available

Midw est Electric's Temporary Pow er and Pow er Outlets are a means of providing pow er required by various construction trades, residential sites, and mobile electrical applications. Temporary Pow er and Pow er Outlets offer one or more receptacles, with or without overcurrent protection, disconnecting, metering, and/or pedestal mounting functions, in a single enclosure of G-90 zinc-coated steel. The NEMA 3R rainproof enclosure is lockable and engineered to provide maximum protection against w eather, vandalism, and normal field use.

Copyright Midw est Electric Products, Inc. 2006