



Representative Image

Catalog No. P065F

Description: MIDWEST 60A GD ACD F 10HP PLASTIC N3R

UPC No 784567300079

Home > AC Disconnects > AC Disconnects

Non-Metallic Fusible Disconnects are available in 30 and 60 Ampere models. Pullers are removable or reinstallable in the OFF position for user safety during equipment maintenance. The P065F UL listing includes the ability to field replace the 60 Ampere puller with a 30 Ampere puller (FR352) for installation flexibility. Listed for use as service entrance.

Descriptors

Category	AC Disconnects
----------	----------------

Specifications

Phase	1
Amps	60.0 A
Enclosure	Plastic
Circuit Protection	Fused Pull-Out
Receptacles	None
AIC	10,000
Cabinet Size	6 X 8
Horse Power Rating	10
Neutral Bar	None
Unit Weight	2.0 lb
Volts	240

Classifications

Standard Package	6
Stock Class Code	Stock

Approvals

Certification	UL/CUL
---------------	--------

Publications

Title	Publication No.	Publication Type
MIDWEST 60A GD AC DISCONNECT OUTLINE DRAWING ERMOPLASTIC N3R ENCLOSURE AC Disconnects	P065F	Drawings-Outline and Dimensional
6 pages. MET-006 Rev. B	MET-006A	Brochures

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.