

YDS30LT

by Burndy
Catalog ID: YDS30LT

Prop 65 Notice

Full Tension Splice, 312.8 kcmil 6201, 317 Index



Product Details

General

Connector Type	Splice
Die Index	317
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Trade Name	UNISPLICE™
UPC	781810014950
UPC 12 Digit	7818100149500

Dimensions

Dimension - B Length fraction	7-3/20 in
Dimension - B Length inch	7.15 in
Dimension - L Length Overall mm	366 mm
Dimension - Length Overall inch	14.42 in

Conductor Related

Conductor - AAAC 5005 Size	312.8
Conductor - AAAC 5005 Size Range	312.8 kcmil
Conductor - AAAC 6201 Size	312.8
Conductor - AAAC 6201 Size Range	312.8
Conductor - ACSR Cmpt Size	266.8
Conductor - ACSR Cmpt Size Range	266.8
Conductor - ACSR Str Size	266.8 (26/7) Owl; 266.8 (26/7) Partridge
Conductor - ACSR Str Size Range	266.8 (26/7) Owl-266.8 (26/7) Partridge
Conductor - AL Str Size	266.8
Conductor - AL Str Size Range	266.8
Conductor Type	<ul style="list-style-type: none"> • ACSR C Str-Size • AL C Str-Size

Certifications and Compliance

Certification - CSA Approved	No
------------------------------	----

Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)