

YDS7M9T

by Burndy
Catalog ID: YDS7M9T

Prop 65 Notice

Full Tension Sleeve, 7 #9, 3 #6, 10-3/8 in L, Full-tension splice for Alumoweld transmission lines.

Features: Full-Tension Splice For Alumoweld Transmission Lines, Five Connectors Accommodate Eight Conductor Sizes, Sleeve Is Pre-Filled With PENETROX Joint Compound And Capped, Sleeve is high strength aluminum alloy for optimum corrosion resistance, Die Index: 677 Element A, Tools, Die Set Catalog Number, And (number Of Crimps): Y35, Y750 Tool, U677 Die, (10), Y45 Tool, U677 Die With PT-6515 Adapter, (10), Y46 Tool, U677 Die With PUADP-1 Adapter, (10)



Product Details

General

Application	For Alumoweld Transmission Lines, Sleeve Is High Strength Aluminum Alloy For Optimum Corrosion Resistance
Connector Type	Splice
Die Index	677
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	FULL TENSION SLEEVE, HYSPLICE
Trade Name	HYSPLICE™
Type	YDS-M-T
UPC	781810015438

Dimensions

Dimension - B Length fraction	5-7/50 in
Dimension - B Length inch	5.14 in
Dimension - L Length Overall mm	264 mm
Dimension - Length Overall inch	10.41 in
Dimension - Outside Diameter inch	0.8 in

Conductor Related

Conductor - AWAC Size	2
Conductor - Alumoweld Size	7#9;3#6
Conductor - Alumoweld Size Range	7#9;3#6

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No

Industry Standard(s)	RUS
Standards - Industry Standards Met	RUS
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)