


YCS39R

by Burndy
Catalog ID: YCS39R

Prop 65 Notice

HYSPLICE AL sleeve with staked cable stop, designed to withstand jumper loop tensile and vibration stresses. ANSI C119.4 CLASS 2 (PARTIAL TENSION), 10-3/4 IN L



Product Details

General

Connector Type	Splice
Die Index	608
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Trade Name	HYSPLICE™
UPC	781810015070
UPC 12 Digit	7818100150700

Dimensions

Dimension - B Length fraction	5-22/71 in
Dimension - B Length inch	5.31 in
Dimension - L Length Overall mm	273 mm
Dimension - Length Overall inch	10.75 in

Conductor Related

Conductor - AAAC 5005 Size	652.4 (19)
Conductor - AAAC 5005 Size Range	652.4 (19) kcmil
Conductor - AAAC 6201 Size	652.4 (19)
Conductor - AAAC 6201 Size Range	652.4 (19)
Conductor - ACSR Str Size	556.5 (24/7) Parakeet;556.5 (26/7) Dove
Conductor - ACSR Str Size Range	556.5 (24/7) Parakeet-556.5 (26/7) Dove
Conductor - AL Str Size	556.5
Conductor - AL Str Size Range	556.5

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No

Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	10
-----------------------	----

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)