

YNA7M8T

by Burndy
Catalog ID: YNA7M8T

Prop 65 Notice

Al Comp Static Wire Terminal, 2 Hole, 7 #8, 3 #5(Alumoweld), 3/8" Steel, 7 Str, 7 #8, 3 #5(Alumoweld), 3/8" Steel, 7 Str.

Features: Compression Terminal, Tools, Die Set Catalog Number, And (number Of Crimps): Y35, Y750 Tool, U688 Die, (7), Y45 Tool, U688 Die With PT-6515 Adapter, (7), Y46 Tool, U688 Die With PUADP-1 Adapter, (7), Y60BHU Tool, L723 Die, Die Index: 668 Or 723, Conductor Type: Alumoweld, EHS Steel



Product Details

General

Application	For Alumoweld And EHS Steel
Connector Type	Terminal
Construction Material - Main	Aluminum
Die Index	668;723
Material	Aluminum
Material Type - Sleeve	Aluminum
Physical Attribute - Pad Orientation	Straight
Prefilled Oxide Inhibitor	Y
Sub Brand	TERMINALS, HYLUG
Type	YNA-M-T, Terminal
UPC	781810016138
UPC 12 Digit	7818100161388

Dimensions

Dimension - B Length inch	3.49 in
Dimension - Bolt Hole Size inch	0.56 in
Dimension - E Spacing between Holes fraction	1-3/4 in
Dimension - L Length Overall mm	249 mm
Dimension - Length Overall inch	9.81 in
Dimension - Outside Diameter inch	0.88 in
Dimension - Pad Width inch	1.5 in

Conductor Related

Conductor - Galvanized Steel Str Size	3/8 (7) in
Conductor - Galvanized Steel Str Size Range	3/8 (7) in
Conductor Type	GAL Steel C Str-Size

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No

Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)