

# YDS326R

by Burndy  
Catalog ID: YDS326R

Prop 65 Notice

2-piece, full tension ACSR splice consists of steel inner sleeve and AL outer sleeve, Inner Sleeve: 6.25 IN L, Outer Sleeve: 26.38 IN L



## Product Details

### General

Connector Type	Splice
Die Index	253;261
Die Index - Element A	253
Die Index - Element B	261
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Trade Name	HYSPLICE™
UPC	781810015964
UPC 12 Digit	7818100159644

### Dimensions

Dimension - Aluminum Sleeve Length inch	26.375 in
Dimension - L Length Overall mm	672 mm
Dimension - Length Overall inch	26.44 in
Dimension - Outside Diameter inch	1.36 in
Dimension - Steel Sleeve Length inch	6.25 in

### Conductor Related

Conductor - ACSR Str Size	477.0 (24/7) Flicker;477.0 (26/7) Hawk;477.0 (30/7) Hen
Conductor - ACSR Str Size Range	477.0 (24/7) Flicker-477.0 (30/7) Hen
Conductor Type	<ul style="list-style-type: none"> <li>• ACSR C Str-Size</li> <li>• AL C Str-Size</li> </ul>

### Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	EX
UL Listed	No

## Logistics

Minimum Pack Quantity	1
-----------------------	---

**For further technical assistance, please contact us**

**BURNDY Headquarters**

47 East Industrial Park Drive  
Manchester, New Hampshire 03109

**Customer Service Hours:**

8 AM - 8 PM Eastern Monday-Friday  
Emergency Service 24-hours/365 Days  
Phone: 1-800-346-4175  
1-603-647-5299 (International)