



YDS27RLY

by Burndy
Catalog ID: YDS27RLY

Prop 65 Notice

AL Compression Splices - Single Sleeve Full Tension, Accommodates:
AAC, ACSR and AAAC, Length: 21 IN L

Product Details

General

Connector Type	Splice
Die Index	658
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Trade Name	UNISPLICE™
UPC	781810015568
UPC 12 Digit	7818100155688

Dimensions

Dimension - B Length fraction	10-11/25 in
Dimension - B Length inch	10.44 in
Dimension - L Length Overall mm	533 mm
Dimension - Length Overall inch	21 in
Dimension - Outside Diameter inch	0.91 in

Conductor Related

Conductor - AAAC 5005 Size	195.7 (7) kcmil
Conductor - AAAC 5005 Size Range	195.7 (7) kcmil
Conductor - AAAC 6201 Size	195.7 (7) kcmil
Conductor - AAAC 6201 Size Range	195.7 (7) kcmil
Conductor - ACSR Str Size	3/0 (6/1) Pigeon AWG
Conductor - ACSR Str Size Range	3/0 (6/1) Pigeon AWG
Conductor - AL Str Size	3/0 AWG
Conductor - AL Str Size Range	3/0 AWG
Conductor Type	<ul style="list-style-type: none"> • ACSR C Str-Size • AL C Str-Size

Certifications and Compliance

Certification - CSA Approved	No
------------------------------	----

Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)