

# YDS32LT

by Burndy  
Catalog ID: YDS32LT

Prop 65 Notice

Full Tension Splice, 394.5 kcmil 6201, 394.5 kcmil 5005 (336.4 E.C. Equiv.), 642 Index

Eliminates strand stripping, installing separate steel sleeve and filling with joint compound



## Product Details

### General

Application	Pre-filled with PENETROX joint compound, stripsealed and capped to limit oxide growth and to increase the life of the connection
Connector Type	Splice
Construction Material - Main	Aluminum
Die Index	642
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	UNISPLICE
Trade Name	UNISPLICE™
Type	YDS-LT
UPC	781810015667
UPC 12 Digit	7818100156677

### Dimensions

Dimension - Inside Diameter inch	0.78 in
Dimension - L Length Overall mm	432 mm
Dimension - Length Overall inch	17 in
Dimension - Outside Diameter inch	1.38 in

### Conductor Related

Conductor - AAAC 5005 Size	394.5
Conductor - AAAC 5005 Size Range	394.5 kcmil
Conductor - AAAC 6201 Size	394.5
Conductor - AAAC 6201 Size Range	394.5
Conductor Type	<ul style="list-style-type: none"> <li>• ACSR C Str-Size</li> <li>• AL C Str-Size</li> </ul>

### Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No

Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

## Logistics

Minimum Pack Quantity	1
-----------------------	---

**For further technical assistance, please contact us**

**BURNDY Headquarters**

47 East Industrial Park Drive  
Manchester, New Hampshire 03109

**Customer Service Hours:**

8 AM - 8 PM Eastern Monday-Friday  
Emergency Service 24-hours/365 Days  
Phone: 1-800-346-4175  
1-603-647-5299 (International)