

YDS36LT

by Burndy
Catalog ID: YDS36LT

Prop 65 Notice

Full Tension Splice, 559.5 kcmil 6201, 559.5 kcmil 5005 (477 E.C. Equiv.), 667 Index



Product Details

General

Connector Type	Splice
Die Index	667
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Trade Name	UNISPLICE™
UPC	781810015742
UPC 12 Digit	7818100157422

Dimensions

Dimension - L Length Overall mm	406 mm
Dimension - Length Overall inch	16 in

Conductor Related

Conductor - AAAC 5005 Size	559.5 (19) kcmil
Conductor - AAAC 5005 Size Range	559.5 (19) kcmil
Conductor - AAAC 6201 Size	559.5 (19) kcmil
Conductor - AAAC 6201 Size Range	559.5 (19) kcmil
Conductor - ACSR Str Size	477.0 (26/7) Hawk kcmil
Conductor - ACSR Str Size Range	477.0 (26/7) Hawk kcmil
Conductor Type	<ul style="list-style-type: none"> • ACSR C Str-Size • AL C Str-Size

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity

1

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)