



YDS34R

by Burndy
Catalog ID: YDS34R

Prop 65 Notice

2-piece, full tension ACSR splice consists of steel inner sleeve and AL outer sleeve, Inner Sleeve: 6.25 IN L, Outer Sleeve: 25.63 IN L

Product Details

General

Connector Type	Splice
Die Index	253;317
Die Index - Element A	253
Die Index - Element B	317
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Trade Name	HYSPLICE™
UPC	781810015704
UPC 12 Digit	7818100157044

Dimensions

Dimension - Aluminum Sleeve Length inch	25.625 in
Dimension - L Length Overall mm	650 mm
Dimension - Length Overall inch	25.59 in
Dimension - Outside Diameter inch	1.25 in
Dimension - Steel Sleeve Length inch	6.25 in

Conductor Related

Conductor - ACSR Str Size	397.5 (26/7) Ibis;397.5 (30/7) Lark
Conductor - ACSR Str Size Range	397.5 (26/7) Ibis-397.5 (30/7) Lark
Conductor Type	<ul style="list-style-type: none"> ACSR C Str-Size AL C Str-Size

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)