


YDS78

by Burndy
Catalog ID: YDS78

Prop 65 Notice

Copper splice designed to develop full rated breaking strength of hard drawn and medium hard drawn solid copper conductor. ANSI C119.4 Class 1 (Full Tension), Die index:168



Product Details

General

Connector Type	Splice
Die Index	168
Material	Copper
Oxide Inhibitor Type	Penetrox E
Physical Attribute - Number of Crimps Required	3
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Trade Name	HYSPLICE™
UPC	781810014707

Dimensions

Dimension - B Length inch	3.55 in
Dimension - L Length Overall mm	190 mm
Dimension - Length Overall inch	7.47 in
Dimension - Outside Diameter inch	0.86 in

Conductor Related

Conductor - Copper Solid Size	4/0 AWG
-------------------------------	---------

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)