

YDS26F

by Burndy
Catalog ID: YDS26F

Prop 65 Notice

Full-tension copper splice designed for copper and copperweld conductors. ANSI C119.4 Class 1 (Full Tension), Die Index: 552



Product Details

General

Connector Type	Splice
Die Index	552
Material	Copper
Physical Attribute - Number of Crimps Required	6
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	N
Trade Name	HYSPLICE™
UPC	781810014622

Dimensions

Dimension - B Length fraction	4-3/8 in
Dimension - B Length inch	4.37 in
Dimension - L Length Overall mm	234 mm
Dimension - Length Overall inch	9.22 in
Dimension - Outside Diameter inch	0.86 in

Conductor Related

Conductor - Copper Str Size	2/0 F AWG
Conductor - CopperWeld Str Size	2/0 F
Conductor - CopperWeld Str Size Range	2/0 F AWG

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)