


## TYPE CP

### Features

- Manufactured from high conductivity copper alloy
- Compact design
- Range taking
- Re-usable
- Suitable for use in circuits rated 35KV or less, proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

### Benefits

- Provides long lasting reliable contact
- Saves space and reduces installation time
- Permits inventories to be kept to a minimum
- Provides efficient use and flexibility in the field
- Application versatility



Catalog Number	Wire Range	Bolt Size	Stud Hole Size	Dimensions			Hex Size
				L	W	H	
CP-8	8-14	10	13/64	51/64	3/8	27/64	Slot
CP-4	4-14	1/4	17/64	1-3/32	17/32	35/64	Slot
CP-0	1/0-8	5/16	11/32	1-1/2	3/4	5/8	1/4
CP-250	250kcmil-6	3/8	13/32	1-31/32	15/16	1-1/16	1/4
CP-500*	500kcmil-4/0	1/2	17/32	2-31/32	1-3/8	1-7/16	3/8
CP-1000*	1000kcmil-500kcmil	1/2	17/32	3-31/32	2-1/32	2-3/16	1/2

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

\* Not CSA Certified

Tested to UL 486A/B, UL File E6207